



PRODUCT MANUAL

Barracuda 7200.10 Serial ATA

| | |
|-------------|-------------|
| ST3750640AS | ST3250410AS |
| ST3750840AS | ST3250310AS |
| ST3500630AS | ST3200820AS |
| ST3500830AS | ST3160815AS |
| ST3400620AS | ST3160215AS |
| ST3400820AS | ST3120815AS |
| ST3320620AS | ST3120215AS |
| ST3320820AS | ST380815AS |
| ST3300620AS | ST380215AS |
| ST3300820AS | ST340815AS |
| ST3250620AS | ST340215AS |
| ST3250820AS | |

Revision history

| Revision | Date | Sheets affected or comments |
|----------|----------|---|
| Rev. A | 05/01/06 | Initial release. |
| Rev. B | 07/20/06 | 1, 3, 14-15, 26-28, 33, 35 and 49 |
| Rev. C | 08/14/06 | 10, 12, 14, 16, 19 and 27-28. |
| Rev. D | 09/26/06 | Added 160 - 40GB models |
| Rev. E | 10/04/06 | 19, 21, 23, 25 and 35 |
| Rev. F | 04/23/07 | Front cover, 1, 3, 14-15, 26-29, 33, 35, 41-42, 49 and 53-56. Added ST3250410AS and ST3250310AS models |

Copyright © 2006-2007 Seagate Technology LLC. All rights reserved. Printed in U.S.A.

Publication number: 100402371, Rev. F April 2007

Seagate, Seagate Technology and the Wave logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Barracuda, SeaTools and SeaTDD are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners.

One gigabyte, or GB, equals one billion bytes when referring to hard drive capacity. Accessible capacity may vary depending on operating environment and formatting. Quantitative usage examples for various applications are for illustrative purposes. Actual quantities will vary based on various factors, including file size, file format, features and application software. Seagate reserves the right to change, without notice, product offerings or specifications.

Contents

| | | |
|------------|---|-----------|
| 1.0 | Introduction | 1 |
| 1.1 | About the Serial ATA interface | 2 |
| 2.0 | Drive specifications | 3 |
| 2.1 | Specification summary tables | 3 |
| 2.2 | Formatted capacity | 26 |
| 2.2.1 | LBA mode | 26 |
| 2.3 | Default logical geometry | 27 |
| 2.4 | Recording and interface technology | 27 |
| 2.5 | Physical characteristics | 28 |
| 2.6 | Seek time | 29 |
| 2.7 | Start/stop times | 29 |
| 2.8 | Power specifications | 30 |
| 2.8.1 | Power consumption | 30 |
| 2.8.2 | Conducted noise | 31 |
| 2.8.3 | Voltage tolerance | 31 |
| 2.8.4 | Power-management modes | 32 |
| 2.9 | Environmental specifications | 33 |
| 2.9.1 | Ambient temperature | 33 |
| 2.9.2 | Temperature gradient | 33 |
| 2.9.3 | Humidity | 33 |
| 2.9.4 | Altitude | 33 |
| 2.9.5 | Shock | 33 |
| 2.9.6 | Vibration | 34 |
| 2.10 | Acoustics | 35 |
| 2.11 | Electromagnetic immunity | 35 |
| 2.12 | Reliability | 36 |
| 2.12.1 | Annualized Failure Rate (AFR) and Mean Time Between Failures (MTBF) | 36 |
| 2.13 | Agency certification | 36 |
| 2.13.1 | Safety certification | 36 |
| 2.13.2 | Electromagnetic compatibility | 36 |
| 2.13.3 | FCC verification | 37 |
| 2.14 | Environmental protection | 37 |
| 2.14.1 | European Union Restriction of Hazardous Substances (RoHS) | 38 |
| 2.15 | Corrosive environment | 38 |
| 3.0 | Configuring and mounting the drive | 39 |
| 3.1 | Handling and static-discharge precautions | 39 |
| 3.2 | Configuring the drive | 40 |
| 3.3 | Serial ATA cables and connectors | 40 |
| 3.4 | Drive mounting | 41 |
| 4.0 | Serial ATA (SATA) interface | 43 |
| 4.1 | Hot-Plug compatibility | 43 |
| 4.2 | Serial ATA device plug connector pin definitions | 44 |
| 4.3 | Supported ATA commands | 45 |
| 4.3.1 | Identify Device command | 47 |
| 4.3.2 | Set Features command | 51 |
| 4.3.3 | S.M.A.R.T. commands | 52 |
| 5.0 | Seagate Technology support services | 53 |

List of Figures

| | | |
|-----------|---|----|
| Figure 1. | Typical 5V startup and operation current profile | 31 |
| Figure 2. | Typical 12V startup and operation current profile | 31 |
| Figure 3. | Serial ATA connectors | 40 |
| Figure 4. | Attaching SATA cabling | 40 |
| Figure 5. | Mounting dimensions for 750-200 GB models (except ST3250410AS and ST3250310AS models) | 41 |
| Figure 6. | Mounting dimensions for 160-40 GB models (including ST3250410AS and ST3250310AS models) | 42 |

1.0 Introduction

This manual describes the functional, mechanical and interface specifications for the following Seagate Barracuda® 7200.10 Serial ATA model drives:

| | | | |
|-------------|-------------|-------------|-------------|
| ST3750640AS | ST3320620AS | ST3250410AS | ST3120215AS |
| ST3750840AS | ST3320820AS | ST3250310AS | ST380815AS |
| ST3500630AS | ST3300620AS | ST3200820AS | ST380215AS |
| ST3500830AS | ST3300820AS | ST3160815AS | ST340815AS |
| ST3400620AS | ST3250620AS | ST3160215AS | ST340215AS |
| ST3400820AS | ST3250820AS | ST3120815AS | |

These drives provide the following key features:

- 7,200 RPM spindle speed.
- High instantaneous (burst) data-transfer rates (up to 300 Mbytes per second).
- Perpendicular recording, Tunneling Giant Magnetoresistive (TGMR) recording heads and EPRML technology, for increased areal density.
- State-of-the-art cache and on-the-fly error-correction algorithms.
- Native Command Queueing with command ordering to increase performance in demanding applications.
- Full-track multiple-sector transfer capability without local processor intervention.
- Quiet operation.
- SeaTools diagnostic software performs a drive self-test that eliminates unnecessary drive returns.
- Support for S.M.A.R.T. drive monitoring and reporting.
- Supports latching SATA cables and connectors.

1.1 About the Serial ATA interface

The Serial ATA interface provides several advantages over the traditional (parallel) ATA interface. The primary advantages include:

- Easy installation and configuration with true plug-and-play connectivity. It is not necessary to set any jumpers or other configuration options.
- Thinner and more flexible cabling for improved enclosure airflow and ease of installation.
- Scalability to higher performance levels.

In addition, Serial ATA makes the transition from parallel ATA easy by providing legacy software support. Serial ATA was designed to allow you to install a Serial ATA host adapter and Serial ATA disc drive in your current system and expect all of your existing applications to work as normal.

The Serial ATA interface connects each disc drive in a point-to-point configuration with the Serial ATA host adapter. There is no master/slave relationship with Serial ATA devices like there is with parallel ATA. If two drives are attached on one Serial ATA host adapter, the host operating system views the two devices as if they were both “masters” on two separate ports. This essentially means both drives behave as if they are Device 0 (master) devices.

Note. The host adapter may, optionally, emulate a master/slave environment to host software where two devices on separate Serial ATA ports are represented to host software as a Device 0 (master) and Device 1 (slave) accessed at the same set of host bus addresses. A host adapter that emulates a master/slave environment manages two sets of shadow registers. This is not a typical Serial ATA environment.

The Serial ATA host adapter and drive share the function of emulating parallel ATA device behavior to provide backward compatibility with existing host systems and software. The Command and Control Block registers, PIO and DMA data transfers, resets, and interrupts are all emulated.

The Serial ATA host adapter contains a set of registers that shadow the contents of the traditional device registers, referred to as the Shadow Register Block. All Serial ATA devices behave like Device 0 devices. For additional information about how Serial ATA emulates parallel ATA, refer to the “Serial ATA: High Speed Serialized AT Attachment” specification. The specification can be downloaded from www.serialata.org.

2.0 Drive specifications

Unless otherwise noted, all specifications are measured under ambient conditions, at 25°C, and nominal power. For convenience, the phrases *the drive* and *this drive* are used throughout this manual to indicate the following drive models:

| | | | |
|-------------|-------------|-------------|-------------|
| ST3750640AS | ST3320620AS | ST3250410AS | ST3120215AS |
| ST3750840AS | ST3320820AS | ST3250310AS | ST380815AS |
| ST3500630AS | ST3300620AS | ST3200820AS | ST380215AS |
| ST3500830AS | ST3300820AS | ST3160815AS | ST340815AS |
| ST3400620AS | ST3250620AS | ST3160215AS | ST340215AS |
| ST3400820AS | ST3250820AS | ST3120815AS | |

2.1 Specification summary tables

The specifications listed in the following tables are for quick reference. For details on specification measurement or definition, see the appropriate section of this manual.

Table 1: Drive specifications summary for 750 Gbyte models

| Drive specification | ST3750640AS | ST3750840AS |
|---|---|-------------|
| Formatted capacity (512 bytes/sector)* | 750 Gbytes | |
| Guaranteed sectors | 1,465,149,168 | |
| Heads | 8 | |
| Discs | 4 | |
| Bytes per sector | 512 | |
| Default sectors per track | 63 | |
| Default read/write heads | 16 | |
| Default cylinders | 16,383 | |
| Recording density | 926 kbits/in max | |
| Track density | 145 ktracks/in avg | |
| Areal density | 128.2 Gbits/in ² avg | |
| Spindle speed | 7,200 RPM | |
| Internal data transfer rate | 1,030 Mbits/sec max | |
| Sustained data transfer rate OD | 78 Mbytes/sec max | |
| I/O data-transfer rate | 300 Mbytes/sec max | |
| ATA data-transfer modes supported | PIO modes 0–4 Multiword DMA modes 0–2 Ultra DMA modes 0–6 | |
| Cache buffer | 16 Mbytes | 8 Mbytes |
| Height (max) | 26.1 mm (1.028 inches) | |
| Width (max) | 101.6 mm (4.000 inches) +/- 0.010 inches | |
| Length (max) | 146.99 mm (5.787 inches) | |
| Weight (typical) | 720 grams (1.59 lbs) | |
| Average latency | 4.16 msec | |
| Power-on to ready | 15 sec max | |
| Standby to ready | 15 sec max | |
| Track-to-track seek time | <0.8 msec typical read; <1.0 msec typical write | |
| Average seek, read | <8.5 msec typical | |
| Average seek, write | <10.0 msec typical | |
| Startup current (typical) 12V (peak) | 2.8 amps | |
| Voltage tolerance (including noise) | 5V ± 5% 12V ± 10% | |
| Ambient temperature | 0° to 60°C (operating) –40° to 70°C (nonoperating) | |
| Temperature gradient | 20°C per hour max (operating) 30°C per hour max (nonoperating) | |
| Relative humidity | 5% to 90% (operating) 5% to 95% (nonoperating) | |
| Relative humidity gradient | 30% per hour max | |
| Wet bulb temperature | 37.7°C max (operating) 37.7°C max (nonoperating) | |
| Altitude, operating | –60.96 m to 3,048 m (–200 ft. to 10,000+ ft.) | |
| Altitude, nonoperating (below mean sea level, max) | –60.96 m to 12,192 m (–200 ft. to 40,000+ ft.) | |
| Operational Shock | 68 Gs at 2 msec max | |
| Non-Operational Shock | 300 Gs at 2 msec max | |

| Drive specification | ST3750640AS | ST3750840AS |
|--|---|-------------|
| Vibration, operating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 0.50 Gs 350–500 Hz:: 0.25 Gs | |
| Vibration, nonoperating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 5.0 Gs 350–500 Hz:: 1.0 Gs | |
| Drive acoustics, sound power | | |
| Idle** | 2.8 bels (typical) 3.0 bels (max) | |
| Performance seek | 3.7 bels (typical) 3.9 bels (max) | |
| Nonrecoverable read errors | 1 per 10 ¹⁴ bits read | |
| Annualized Failure Rate (AFR) | 0.34% | |
| Warranty | 5 years on distribution units. To determine the warranty for a specific drive, use a web browser to access the following web page: www.seagate.com/support/service/ From this page, click on the “Verify Your Warranty” link. You will be asked to provide the drive serial number, model number (or part number) and country of purchase. The system will display the warranty information for your drive. | |
| Contact start-stop cycles | 50,000 at 25°C, 50% rel. humidity | |
| Supports Hotplug operation per the Serial ATA Revision 2.5 specification | Yes | |

*One Gbyte equals one billion bytes when referring to hard drive capacity. Accessible capacity may vary depending on operating environment and formatting.

**During periods of drive idle, some offline activity may occur according to the S.M.A.R.T. specification, which may increase acoustic and power to operational levels.

Table 2: Drive specifications summary for 500 Gbyte models

| Drive specification | ST3500630AS | ST3500830AS |
|---|---|-------------|
| Formatted capacity (512 bytes/sector)* | 500 Gbytes | |
| Guaranteed sectors | 976,773,168 | |
| Heads | 6 | |
| Discs | 3 | |
| Bytes per sector | 512 | |
| Default sectors per track | 63 | |
| Default read/write heads | 16 | |
| Default cylinders | 16,383 | |
| Recording density | 813 kbits/in max | |
| Track density | 145 ktracks/in avg | |
| Areal density | 114.4 Gbits/in ² avg | |
| Spindle speed | 7,200 RPM | |
| Internal data transfer rate | 1,030 Mbits/sec max | |
| Sustained data transfer rate OD | 72 Mbytes/sec max | |
| I/O data-transfer rate | 300 Mbytes/sec max | |
| ATA data-transfer modes supported | PIO modes 0–4 Multiword DMA modes 0–2 Ultra DMA modes 0–6 | |
| Cache buffer | 16 Mbytes | 8 Mbytes |
| Height (max) | 26.1 mm (1.028 inches) | |
| Width (max) | 101.6 mm (4.000 inches) +/- 0.010 inches | |
| Length (max) | 146.99 mm (5.787 inches) | |
| Weight (typical) | 635 grams (1.40 lbs) | |
| Average latency | 4.16 msec | |
| Power-on to ready | 15 sec max | |
| Standby to ready | 15 sec max | |
| Track-to-track seek time | <0.8 msec typical read; <1.0 msec typical write | |
| Average seek, read | <8.5 msec typical | |
| Average seek, write | <10.0 msec typical | |
| Startup current (typical) 12V (peak) | 2.8 amps | |
| Voltage tolerance (including noise) | 5V ± 5% 12V ± 10% | |
| Ambient temperature | 0° to 60°C (operating) –40° to 70°C (nonoperating) | |
| Temperature gradient (max) | 20°C per hour (operating) 30°C per hour (nonoperating) | |
| Relative humidity | 5% to 90% (operating) 5% to 95% (nonoperating) | |
| Relative humidity gradient | 30% per hour max | |
| Wet bulb temperature (max) | 37.7 °C (operating) 37.7 °C (nonoperating) | |
| Altitude, operating | –60.96 m to 3,048 m (–200 ft. to 10,000+ ft.) | |
| Altitude, nonoperating (below mean sea level, max) | –60.96 m to 12,192 m (–200 ft. to 40,000+ ft.) | |
| Operational Shock | 68 Gs max at 2 msec | |
| Non-Operational Shock | 300 Gs max at 2 msec | |

| | | |
|--|---|-------------|
| Drive specification | ST3500630AS | ST3500830AS |
| Vibration, operating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 0.50 Gs 350–500 Hz:: 0.25 Gs | |
| Vibration, nonoperating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 5.0 Gs 350–500 Hz:: 1.0 Gs | |
| Drive acoustics, sound power | | |
| Idle** | 2.8 bels (typical) 3.0 bels (max) | |
| Performance seek | 3.7 bels (typical) 3.9 bels (max) | |
| Nonrecoverable read errors | 1 per 10 ¹⁴ bits read | |
| Annualized Failure Rate (AFR) | 0.34% | |
| Warranty | 5 years on distribution units. To determine the warranty for a specific drive, use a web browser to access the following web page: www.seagate.com/support/service/ From this page, click on the “Verify Your Warranty” link. You will be asked to provide the drive serial number, model number (or part number) and country of purchase. The system will display the warranty information for your drive. | |
| Contact start-stop cycles | 50,000 at 25°C, 50% rel. humidity | |
| Supports Hotplug operation per the Serial ATA Revision 2.5 specification | Yes | |

*One Gbyte equals one billion bytes when referring to hard drive capacity. Accessible capacity may vary depending on operating environment and formatting.

**During periods of drive idle, some offline activity may occur according to the S.M.A.R.T. specification, which may increase acoustic and power to operational levels.

Table 3: Drive specifications summary for 400 Gbyte models

| Drive specification | ST3400620AS | ST3400820AS |
|---|---|-------------|
| Formatted capacity (512 bytes/sector)* | 400 Gbytes | |
| Guaranteed sectors | 781,422,768 | |
| Heads | 5 | |
| Doscs | 3 | |
| Bytes per sector | 512 | |
| Default sectors per track | 63 | |
| Default read/write heads | 16 | |
| Default cylinders | 16,383 | |
| Recording density | 781 kbits/in max | |
| Track density | 145 ktracks/in avg | |
| Areal density | 128.2 Gbits/in ² avg | |
| Spindle speed | 7,200 RPM | |
| Internal data transfer rate | 1,030 Mbits/sec max | |
| Sustained data transfer rate OD | 72 Mbytes/sec max | |
| I/O data-transfer rate | 300 Mbytes/sec max | |
| ATA data-transfer modes supported | PIO modes 0–4 Multiword DMA modes 0–2 Ultra DMA modes 0–6 | |
| Cache buffer | 16 Mbytes | 8 Mbytes |
| Height (max) | 26.1 mm (1.028 inches) | |
| Width (max) | 101.6 mm (4.000 inches) +/- 0.010 inches | |
| Length (max) | 146.99 mm (5.787 inches) | |
| Weight (typical) | 635 grams (1.40 lbs) | |
| Average latency | 4.16 msec | |
| Power-on to ready | 15 sec max | |
| Standby to ready | 15 sec max | |
| Track-to-track seek time | <0.8 msec typical read; <1.0 msec typical write | |
| Average seek, read | <8.5 msec typical | |
| Average seek, write | <10.0 msec typical | |
| Startup current (typical) 12V (peak) | 2.8 amps | |
| Voltage tolerance (including noise) | 5V ± 5% 12V ± 10% | |
| Ambient temperature | 0° to 60°C (operating) –40° to 70°C (nonoperating) | |
| Temperature gradient | 20°C per hour max (operating) 30°C per hour max (nonoperating) | |
| Relative humidity | 5% to 90% (operating) 5% to 95% (nonoperating) | |
| Relative humidity gradient | 30% per hour max | |
| Wet bulb temperature | 37.7 °C max (operating) 37.7 °C max (nonoperating) | |
| Altitude, operating | –60.96 m to 3,048 m (–200 ft. to 10,000+ ft.) | |
| Altitude, nonoperating (below mean sea level, max) | –60.96 m to 12,192 m (–200 ft. to 40,000+ ft.) | |
| Operational Shock | 68 Gs max at 2 msec | |
| Non-Operational Shock | 300 Gs max at 2 msec | |

| | | |
|--|---|-------------|
| Drive specification | ST3400620AS | ST3400820AS |
| Vibration, operating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 0.50 Gs 350–500 Hz:: 0.25 Gs | |
| Vibration, nonoperating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 5.0 Gs 350–500 Hz:: 1.0 Gs | |
| Drive acoustics, sound power | | |
| Idle** | 2.7 bels (typical) 2.9 bels (max) | |
| Performance seek | 3.4 bels (typical) 3.6 bels (max) | |
| Nonrecoverable read errors | 1 per 10 ¹⁴ bits read | |
| Annualized Failure Rate (AFR) | 0.34% | |
| Warranty | 5 years on distribution units. To determine the warranty for a specific drive, use a web browser to access the following web page: www.seagate.com/support/service/ From this page, click on the “Verify Your Warranty” link. You will be asked to provide the drive serial number, model number (or part number) and country of purchase. The system will display the warranty information for your drive. | |
| Contact start-stop cycles | 50,000 at 25°C, 50% rel. humidity | |
| Supports Hotplug operation per the Serial ATA Revision 2.5 specification | Yes | |

*One Gbyte equals one billion bytes when referring to hard drive capacity. Accessible capacity may vary depending on operating environment and formatting.

**During periods of drive idle, some offline activity may occur according to the S.M.A.R.T. specification, which may increase acoustic and power to operational levels.

Table 4: Drive specifications summary for 320 Gbyte models

| Drive specification | ST3320620AS | ST3320820AS |
|---|---|-------------|
| Formatted capacity (512 bytes/sector)* | 320 Gbytes | |
| Guaranteed sectors | 625,142,448 | |
| Heads | 4 | |
| Discs | 2 | |
| Bytes per sector | 512 | |
| Default sectors per track | 63 | |
| Default read/write heads | 16 | |
| Default cylinders | 16,383 | |
| Recording density | 781 kbits/in max | |
| Track density | 145 ktracks/in avg | |
| Areal density | 114.4 Gbits/in ² avg | |
| Spindle speed | 7,200 RPM | |
| Internal data transfer rate | 1,030 Mbits/sec max | |
| Sustained data transfer rate OD | 72 Mbytes/sec max | |
| I/O data-transfer rate | 300 Mbytes/sec max | |
| ATA data-transfer modes supported | PIO modes 0–4 Multiword DMA modes 0–2 Ultra DMA modes 0–6 | |
| Cache buffer | 16 Mbytes | 8 Mbytes |
| Height (max) | 26.1 mm (1.028 inches) | |
| Width (max) | 101.6 mm (4.000 inches) +/- 0.010 inches | |
| Length (max) | 146.99 mm (5.787 inches) | |
| Weight (typical) | 635 grams (1.40 lbs) | |
| Average latency | 4.16 msec | |
| Power-on to ready | 15 sec max | |
| Standby to ready | 15 sec max | |
| Track-to-track seek time | <0.8 msec typical read; <1.0 typical write | |
| Average seek, read | <8.5 msec typical | |
| Average seek, write | <10.0 msec typical | |
| Startup current (typical) 12V (peak) | 2.8 amps | |
| Voltage tolerance (including noise) | 5V ± 5% 12V ± 10% | |
| Ambient temperature | 0° to 60°C (operating) –40° to 70°C (nonoperating) | |
| Temperature gradient | 20°C per hour max (operating) 30°C per hour max (nonoperating) | |
| Relative humidity | 5% to 90% (operating) 5% to 95% (nonoperating) | |
| Relative humidity gradient | 30% per hour max | |
| Wet bulb temperature | 37.7°C max (operating) 37.7°C max (nonoperating) | |
| Altitude, operating | –60.96 m to 3,048 m (–200 ft. to 10,000+ ft.) | |
| Altitude, nonoperating (below mean sea level, max) | –60.96 m to 12,192 m (–200 ft. to 40,000+ ft.) | |
| Operational Shock | 68 Gs max at 2 msec | |
| Non-Operational Shock | 350 Gs max at 2 msec | |

| | | |
|--|---|-------------|
| Drive specification | ST3320620AS | ST3320820AS |
| Vibration, operating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 0.50 Gs 350–500 Hz:: 0.25 Gs | |
| Vibration, nonoperating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 5.0 Gs 350–500 Hz:: 1.0 Gs | |
| Drive acoustics, sound power | | |
| Idle** | 2.5 bels (typical) 2.9 bels (max) | |
| Performance seek | 3.0 bels (typical) 3.2 bels (max) | |
| Nonrecoverable read errors | 1 per 10 ¹⁴ bits read | |
| Annualized Failure Rate (AFR) | 0.34% | |
| Warranty | 5 years on distribution units. To determine the warranty for a specific drive, use a web browser to access the following web page: www.seagate.com/support/service/ From this page, click on the “Verify Your Warranty” link. You will be asked to provide the drive serial number, model number (or part number) and country of purchase. The system will display the warranty information for your drive. | |
| Contact start-stop cycles | 50,000 at 25°C, 50% rel. humidity | |
| Supports Hotplug operation per the Serial ATA Revision 2.5 specification | Yes | |

*One Gbyte equals one billion bytes when referring to hard drive capacity. Accessible capacity may vary depending on operating environment and formatting.

**During periods of drive idle, some offline activity may occur according to the S.M.A.R.T. specification, which may increase acoustic and power to operational levels.

Table 5: Drive specifications summary for 300 Gbyte models

| Drive specification | ST3300620AS | ST3300820AS |
|---|---|-------------|
| Formatted capacity (512 bytes/sector)* | 300 Gbytes | |
| Guaranteed sectors | 586,072,368 | |
| Heads | 3 | |
| Discs | 2 | |
| Bytes per sector | 512 | |
| Default sectors per track | 63 | |
| Default read/write heads | 16 | |
| Default cylinders | 16,383 | |
| Recording density | 781 kbits/in max | |
| Track density | 145 ktracks/in avg | |
| Areal density | 114.4 Gbits/in ² avg | |
| Spindle speed | 7,200 RPM | |
| Internal data transfer rate | 1,030 Mbits/sec max | |
| Sustained data transfer rate OD | 72 Mbytes/sec max | |
| I/O data-transfer rate | 300 Mbytes/sec max | |
| ATA data-transfer modes supported | PIO modes 0–4 Multiword DMA modes 0–2 Ultra DMA modes 0–6 | |
| Cache buffer | 16 Mbytes | 8 Mbytes |
| Height (max) | 26.1 mm (1.028 inches) | |
| Width (max) | 101.6 mm (4.000 inches) +/- 0.010 inches | |
| Length (max) | 146.99 mm (5.787 inches) | |
| Weight (typical) | 600 grams (1.32 lb.) | |
| Average latency | 4.16 msec | |
| Power-on to ready | 11 sec max | |
| Standby to ready | 15 sec max | |
| Track-to-track seek time | <0.8 msec typical read; <1.0 msec typical write | |
| Average seek, read | <8.5 msec typical | |
| Average seek, write | <10.0 msec typical | |
| Startup current (typical) 12V (peak) | 2.8 amps | |
| Voltage tolerance (including noise) | 5V ± 5% 12V ± 10% | |
| Ambient temperature | 0° to 60°C (operating) –40° to 70°C (nonoperating) | |
| Temperature gradient | 20°C per hour max (operating) 30°C per hour max (nonoperating) | |
| Relative humidity | 5% to 90% (operating) 5% to 95% (nonoperating) | |
| Relative humidity gradient | 30% per hour max | |
| Wet bulb temperature | 37.7°C max (operating) 37.7°C max (nonoperating) | |
| Altitude, operating | –60.96 m to 3,048 m (–200 ft. to 10,000+ ft.) | |
| Altitude, nonoperating (below mean sea level, max) | –60.96 m to 12,192 m (–200 ft. to 40,000+ ft.) | |
| Operational Shock | 68 Gs max at 2 msec | |
| Non-Operational Shock | 350 Gs max at 2 msec | |

| Drive specification | ST3300620AS | ST3300820AS |
|--|---|-------------|
| Vibration, operating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 0.50 Gs 350–500 Hz:: 0.25 Gs | |
| Vibration, nonoperating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 5.0 Gs 350–500 Hz:: 1.0 Gs | |
| Drive acoustics, sound power | | |
| Idle** | 2.5 bels (typical) 2.9 bels (max) | |
| Performance seek | 3.0 bels (typical) 3.2 bels (max) | |
| Nonrecoverable read errors | 1 per 10 ¹⁴ bits read | |
| Annualized Failure Rate (AFR) | 0.34% | |
| Warranty | 5 years on distribution units. To determine the warranty for a specific drive, use a web browser to access the following web page: www.seagate.com/support/service/ From this page, click on the “Verify Your Warranty” link. You will be asked to provide the drive serial number, model number (or part number) and country of purchase. The system will display the warranty information for your drive. | |
| Contact start-stop cycles | 50,000 at 25°C, 50% rel. humidity | |
| Supports Hotplug operation per the Serial ATA Revision 2.5 specification | Yes | |

*One Gbyte equals one billion bytes when referring to hard drive capacity. Accessible capacity may vary depending on operating environment and formatting.

**During periods of drive idle, some offline activity may occur according to the S.M.A.R.T. specification, which may increase acoustic and power to operational levels.

Table 6: Drive specifications summary for 250 Gbyte models

| Drive specification | ST3250620AS | ST3250820AS | ST3250410AS | ST3250310AS |
|---|---|-------------|--|-------------|
| Formatted capacity (512 bytes/sector)* | 250 Gbytes | | | |
| Guaranteed sectors | 488,397,168 | | | |
| Heads | 3 | | 2 | |
| Discs | 2 | | 1 | |
| Bytes per sector | 512 | | | |
| Default sectors per track | 63 | | | |
| Default read/write heads | 16 | | | |
| Default cylinders | 16,383 | | | |
| Recording density | 813 kbits/in max | | 1090 kbits/in max | |
| Track density | 145 ktracks/in avg | | 150 ktracks/in avg | |
| Areal density | 114.4 Gbits/in ² avg | | 164 Gbits/in ² avg | |
| Spindle speed | 7,200 RPM | | | |
| Internal data transfer rate | 1,030 Mbits/sec max | | 1,287 Mbits/sec max | |
| Sustained data transfer rate OD | 72 Mbytes/sec max | | 110 Mbytes/sec max | |
| I/O data-transfer rate | 300 Mbytes/sec max | | | |
| ATA data-transfer modes supported | PIO modes 0–4 Multiword DMA modes 0–2 Ultra DMA modes 0–6 | | | |
| Cache buffer | 16 Mbytes | 8 Mbytes | 16 Mbytes | 8 Mbytes |
| Height (max) | 26.1 mm (1.028 inches) | | 19.99 mm (.787 inches) | |
| Width (max) | 101.6 mm (4.000 inches) +/- 0.010 inches | | | |
| Length (max) | 146.99 mm (5.787 inches) | | | |
| Weight (typical) | 600 grams (1.32 lb.) | | 382 grams (0.842 lb.) | |
| Average latency | 4.16 msec | | | |
| Power-on to ready | 11 sec max | | | |
| Standby to ready | 15 sec max | | | |
| Track-to-track seek time | <0.8 msec typical read, <1.0 msec typical write | | <1.0 msec typical read, <1.2 msec typical write | |
| Average seek, read | <8.5 msec typical | | | |
| Average seek, write | <10.0 msec typical | | | |
| Startup current (typical) 12V (peak) | 2.8 amps | | 2.0 amps | |
| Voltage tolerance (including noise) | 5V ± 5% 12V ± 10% | | | |
| Ambient temperature | 0° to 60°C per hour max (operating) –40° to 70°C per hour max (nonoperating) | | | |
| Temperature gradient | 20°C (operating) 30°C (nonoperating) | | | |
| Relative humidity | 5% to 90% (operating) 5% to 95% (nonoperating) | | | |
| Relative humidity gradient | 30% per hour max | | | |
| Wet bulb temperature | 37.7°C max (operating) 37.7°C max (nonoperating) | | | |
| Altitude, operating | –60.96 m to 3,048 m (–200 ft. to 10,000+ ft.) | | | |
| Altitude, nonoperating (below mean sea level, max) | –60.96 m to 12,192 m (–200 ft. to 40,000+ ft.) | | | |
| Operational Shock | 68 Gs max at 2 msec | | 63 Gs max at 2 msec | |
| Non-Operational Shock | 350 Gs max at 2 msec | | | |

| Drive specification | ST3250620AS | ST3250820AS | ST3250410AS | ST3250310AS |
|--|---|-------------|--------------------------------------|-------------|
| Vibration, operating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 0.50 Gs 350–500 Hz:: 0.25 Gs | | | |
| Vibration, nonoperating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 5.0 Gs 350–500 Hz:: 1.0 Gs | | | |
| Drive acoustics, sound power | | | | |
| Idle** | 2.5 bels (typical) 2.9 bels (max) | | 2.8 bels (typical) 2.9 bels (max) | |
| Performance seek | 3.0 bels (typical) 3.2 bels (max) | | | |
| Quiet seek | | | 3.0 bels (typical) 3.1 bels (max) | |
| Nonrecoverable read errors | 1 per 10 ¹⁴ bits read | | | |
| Annualized Failure Rate (AFR) | 0.34% | | | |
| Warranty | 5 years on distribution units. To determine the warranty for a specific drive, use a web browser to access the following web page: www.seagate.com/support/service/ From this page, click on the “Verify Your Warranty” link. You will be asked to provide the drive serial number, model number (or part number) and country of purchase. The system will display the warranty information for your drive. | | | |
| Contact start-stop cycles | 50,000 at 25°C, 50% rel. humidity | | | |
| Supports Hotplug operation per the Serial ATA Revision 2.5 specification | Yes | | | |

*One Gbyte equals one billion bytes when referring to hard drive capacity. Accessible capacity may vary depending on operating environment and formatting.

**During periods of drive idle, some offline activity may occur according to the S.M.A.R.T. specification, which may increase acoustic and power to operational levels.

Table 7: Drive specifications summary for the 200 Gbyte mode

| | |
|---|---|
| Drive specification | ST3200820AS |
| Formatted capacity (512 bytes/sector)* | 200 Gbytes |
| Guaranteed sectors | 390,721,968 |
| Heads | 3 |
| Discs | 2 |
| Bytes per sector | 512 |
| Default sectors per track | 63 |
| Default read/write heads | 16 |
| Default cylinders | 16,383 |
| Recording density | 813 kbits/in max |
| Track density | 145 ktracks/in avg |
| Areal density | 114.4 Gbits/in ² avg |
| Spindle speed | 7,200 RPM |
| Internal data transfer rate | 1,030 Mbits/sec max |
| Sustained data transfer rate OD | 72 Mbytes/sec max |
| I/O data-transfer rate | 300 Mbytes/sec max |
| ATA data-transfer modes supported | PIO modes 0–4 Multiword DMA modes 0–2 Ultra DMA modes 0–6 |
| Cache buffer | 8 Mbytes |
| Height (max) | 26.1 mm (1.028 inches) |
| Width (max) | 101.6 mm (4.000 inches) +/- 0.010 inches |
| Length (max) | 146.99 mm (5.787 inches) |
| Weight (typical) | 600 grams (1.32 lb.) |
| Average latency | 4.16 msec |
| Power-on to ready | 11 sec max |
| Standby to ready | 15 sec max |
| Track-to-track seek time | <0.8 msec typical read; <1.0 msec typical write |
| Average seek, read | <8.5 msec typical |
| Average seek, write | <10.0 msec typical |
| Startup current (typical) 12V (peak) | 2.8 amps |
| Voltage tolerance (including noise) | 5V ± 5% 12V ± 10% |
| Ambient temperature | 0° to 60°C (operating) –40° to 70°C (nonoperating) |
| Temperature gradient | 20°C per hour max (operating) 30°C per hour max (nonoperating) |
| Relative humidity | 5% to 90% (operating) 5% to 95% (nonoperating) |
| Relative humidity gradient | 30% per hour max |
| Wet bulb temperature | 37.7°C max (operating) 37.7°C max (nonoperating) |
| Altitude, operating | –60.96 m to 3,048 m (–200 ft. to 10,000+ ft.) |
| Altitude, nonoperating (below mean sea level, max) | –60.96 m to 12,192 m (–200 ft. to 40,000+ ft.) |
| Operational Shock | 68 Gs max at 2 msec |
| Non-Operational Shock | 350 Gs max at 2 msec |

| | |
|--|--|
| Drive specification | ST3200820AS |
| Vibration, operating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 0.5 Gs 350–500 Hz:: 0.25 Gs |
| Vibration, nonoperating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 5.0 Gs 350–500 Hz:: 1.0 Gs |
| Drive acoustics, sound power | |
| Idle** | 2.5 bels (typical) 2.9 bels (max) |
| Performance seek | 3.0 bels (typical) 3.2 bels (max) |
| Nonrecoverable read errors | 1 per 10 ¹⁴ bits read |
| Annualized Failure Rate (AFR) | 0.34% |
| Warranty | 5 years on distribution units. To determine the warranty for a specific drive, use a web browser to access the following web page: www.seagate.com/support/service/ From this page, click on the “Verify Your Warranty” link. You will be asked to provide the drive serial number, model number (or part number) and country of purchase. The system will display the warranty information for your drive. |
| Contact start-stop cycles | 50,000 at 25°C, 50% rel. humidity |
| Supports Hotplug operation per the Serial ATA Revision 2.5 specification | Yes |

*One Gbyte equals one billion bytes when referring to hard drive capacity. Accessible capacity may vary depending on operating environment and formatting.

**During periods of drive idle, some offline activity may occur according to the S.M.A.R.T. specification, which may increase acoustic and power to operational levels.

Table 8: Drive specifications summary for the 160 Gbyte models

| Drive specification | ST3160815AS | ST3160215AS |
|---|---|-------------|
| Formatted capacity (512 bytes/sector)* | 160 Gbytes | |
| Guaranteed sectors | 312,581,808 | |
| Heads | 2 | |
| Discs | 1 | |
| Bytes per sector | 512 | |
| Default sectors per track | 63 | |
| Default read/write heads | 16 | |
| Default cylinders | 16,383 | |
| Recording density | 824 kbits/in max | |
| Track density | 137.259 ktracks/in avg | |
| Areal density | 101 Gbits/in ² avg | |
| Spindle speed | 7,200 RPM | |
| Internal data transfer rate | 930 Mbits/sec max | |
| Sustained data transfer rate OD | 78 Mbytes/sec max | |
| I/O data-transfer rate | 300 Mbytes/sec max | |
| ATA data-transfer modes supported | PIO modes 0–4 Multiword DMA modes 0–2 Ultra DMA modes 0–6 | |
| Cache buffer | 8 Mbytes | 2 Mbytes |
| Height (max) | 19.99 mm (0.787 inches) | |
| Width (max) | 101.6 mm (4.000 inches) +/- 0.010 inches | |
| Length (max) | 146.99 mm (5.787 inches) | |
| Weight (typical) | 380 grams (0.838 lb.) | |
| Average latency | 4.16 msec | |
| Power-on to ready | 7.9 sec max | |
| Standby to ready | 7.9 sec max | |
| Track-to-track seek time | <1.0 msec typical read; <1.2 msec typical write | |
| Average seek, read | <11 msec typical | |
| Average seek, write | <12 msec typical | |
| Startup current (typical) 12V (peak) | 2.8 amps | |
| Voltage tolerance (including noise) | 5V ± 5% 12V ± 10% | |
| Ambient temperature | 0° to 60°C (operating) –40° to 75°C (nonoperating) | |
| Temperature gradient | 20°C per hour max (operating) 30°C per hour max (nonoperating) | |
| Relative humidity | 5% to 90% (operating) 5% to 95% (nonoperating) | |
| Relative humidity gradient | 30% per hour max | |
| Wet bulb temperature | 37.7°C max (operating) 40°C max (nonoperating) | |
| Altitude, operating | –60.96 m to 3,048 m (–200 ft. to 10,000+ ft.) | |
| Altitude, nonoperating (below mean sea level, max) | –60.96 m to 12,192 m (–200 ft. to 40,000+ ft.) | |
| Operational Shock | 63 Gs max at 2 msec | |
| Non-Operational Shock | 350 Gs max at 2 msec | |

| Drive specification | ST3160815AS | ST3160215AS |
|--|--|-------------|
| Vibration, operating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 0.5 Gs 350–500 Hz:: 0.25 Gs | |
| Vibration, nonoperating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 5.0 Gs 350–500 Hz:: 1.0 Gs | |
| Drive acoustics, sound power | | |
| Idle** | 2.8 bels (typical) 3.0 bels (max) | |
| Quiet seek | 3.0 bels (typical) 3.2 bels (max) | |
| Nonrecoverable read errors | 1 per 10 ¹⁴ bits read | |
| Annualized Failure Rate (AFR) | 0.34% | |
| Warranty | 5 years on distribution units. To determine the warranty for a specific drive, use a web browser to access the following web page: www.seagate.com/support/service/ From this page, click on the “Verify Your Warranty” link. You will be asked to provide the drive serial number, model number (or part number) and country of purchase. The system will display the warranty information for your drive. | |
| Contact start-stop cycles | 50,000 at 25°C, 50% rel. humidity | |
| Supports Hotplug operation per the Serial ATA Revision 2.5 specification | Yes | |

*One Gbyte equals one billion bytes when referring to hard drive capacity. Accessible capacity may vary depending on operating environment and formatting.

**During periods of drive idle, some offline activity may occur according to the S.M.A.R.T. specification, which may increase acoustic and power to operational levels.

Table 9: Drive specifications summary for the 120 Gbyte models

| Drive specification | ST3120815AS | ST3120215AS |
|---|---|-------------|
| Formatted capacity (512 bytes/sector)* | 120 Gbytes | |
| Guaranteed sectors | 234,441,648 | |
| Heads | 2 | |
| Discs | 1 | |
| Bytes per sector | 512 | |
| Default sectors per track | 63 | |
| Default read/write heads | 16 | |
| Default cylinders | 16,383 | |
| Recording density | 824 kbits/in max | |
| Track density | 137.259 ktracks/in avg | |
| Areal density | 101 Gbits/in ² avg | |
| Spindle speed | 7,200 RPM | |
| Internal data transfer rate | 930 Mbits/sec max | |
| Sustained data transfer rate OD | 78 Mbytes/sec max | |
| I/O data-transfer rate | 300 Mbytes/sec max | |
| ATA data-transfer modes supported | PIO modes 0–4 Multiword DMA modes 0–2 Ultra DMA modes 0–6 | |
| Cache buffer | 8 Mbytes | 2 Mbytes |
| Height (max) | 19.99 mm (0.787 inches) | |
| Width (max) | 101.6 mm (4.000 inches) +/- 0.010 inches | |
| Length (max) | 146.99 mm (5.787 inches) | |
| Weight (typical) | 380 grams (0.838 lb.) | |
| Average latency | 4.16 msec | |
| Power-on to ready | 7.9 sec max | |
| Standby to ready | 7.9 sec max | |
| Track-to-track seek time | <1.0 msec typical read; <1.2 msec typical write | |
| Average seek, read | <11 msec typical | |
| Average seek, write | <12 msec typical | |
| Startup current (typical) 12V (peak) | 2.8 amps | |
| Voltage tolerance (including noise) | 5V ± 5% 12V ± 10% | |
| Ambient temperature | 0° to 60°C (operating) –40° to 75°C (nonoperating) | |
| Temperature gradient | 20°C per hour max (operating) 30°C per hour max (nonoperating) | |
| Relative humidity | 5% to 90% (operating) 5% to 95% (nonoperating) | |
| Relative humidity gradient | 30% per hour max | |
| Wet bulb temperature | 37.7°C max (operating) 40°C max (nonoperating) | |
| Altitude, operating | –60.96 m to 3,048 m (–200 ft. to 10,000+ ft.) | |
| Altitude, nonoperating (below mean sea level, max) | –60.96 m to 12,192 m (–200 ft. to 40,000+ ft.) | |
| Operational Shock | 63 Gs max at 2 msec | |
| Non-Operational Shock | 350 Gs max at 2 msec | |

| Drive specification | ST3120815AS | ST3120215AS |
|--|--|-------------|
| Vibration, operating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 0.5 Gs 350–500 Hz:: 0.25 Gs | |
| Vibration, nonoperating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 5.0 Gs 350–500 Hz:: 1.0 Gs | |
| Drive acoustics, sound power | | |
| Idle** | 2.8 bels (typical) 3.0 bels (max) | |
| Quiet seek | 3.0 bels (typical) 3.2 bels (max) | |
| Nonrecoverable read errors | 1 per 10 ¹⁴ bits read | |
| Annualized Failure Rate (AFR) | 0.34% | |
| Warranty | 5 years on distribution units. To determine the warranty for a specific drive, use a web browser to access the following web page: www.seagate.com/support/service/ From this page, click on the “Verify Your Warranty” link. You will be asked to provide the drive serial number, model number (or part number) and country of purchase. The system will display the warranty information for your drive. | |
| Contact start-stop cycles | 50,000 at 25°C, 50% rel. humidity | |
| Supports Hotplug operation per the Serial ATA Revision 2.5 specification | Yes | |

*One Gbyte equals one billion bytes when referring to hard drive capacity. Accessible capacity may vary depending on operating environment and formatting.

**During periods of drive idle, some offline activity may occur according to the S.M.A.R.T. specification, which may increase acoustic and power to operational levels.

Table 10: Drive specifications summary for the 80 Gbyte models

| Drive specification | ST380815AS | ST380215AS |
|---|---|------------|
| Formatted capacity (512 bytes/sector)* | 80 Gbytes | |
| Guaranteed sectors | 156,301,488 | |
| Heads | 1 | |
| Discs | 1 | |
| Bytes per sector | 512 | |
| Default sectors per track | 63 | |
| Default read/write heads | 16 | |
| Default cylinders | 16,383 | |
| Recording density | 824 kbits/in max | |
| Track density | 137.259 ktracks/in avg | |
| Areal density | 101 Gbits/in ² avg | |
| Spindle speed | 7,200 RPM | |
| Internal data transfer rate | 930 Mbits/sec max | |
| Sustained data transfer rate OD | 78 Mbytes/sec max | |
| I/O data-transfer rate | 300 Mbytes/sec max | |
| ATA data-transfer modes supported | PIO modes 0–4 Multiword DMA modes 0–2 Ultra DMA modes 0–6 | |
| Cache buffer | 8 Mbytes | 2 Mbytes |
| Height (max) | 19.99 mm (0.787 inches) | |
| Width (max) | 101.6 mm (4.000 inches) +/- 0.010 inches | |
| Length (max) | 146.99 mm (5.787 inches) | |
| Weight (typical) | 365 grams (0.805 lb.) | |
| Average latency | 4.16 msec | |
| Power-on to read | 7.9 sec max | |
| Standby to ready | 7.9 sec max | |
| Track-to-track seek time | <1.0 msec typical read); <1.2 msec typical write | |
| Average seek, read | <11 msec typical | |
| Average seek, write | <12 msec typical | |
| Startup current (typical) 12V (peak) | 2.8 amps | |
| Voltage tolerance (including noise) | 5V ± 5% 12V ± 10% | |
| Ambient temperature | 0° to 60°C (operating) –40° to 75°C (nonoperating) | |
| Temperature gradient | 20°C per hour max (operating) 30°C per hour max (nonoperating) | |
| Relative humidity | 5% to 90% (operating) 5% to 95% (nonoperating) | |
| Relative humidity gradient | 30% per hour max | |
| Wet bulb temperature | 37.7°C max (operating) 40°C max (nonoperating) | |
| Altitude, operating | –60.96 m to 3,048 m (–200 ft. to 10,000+ ft.) | |
| Altitude, nonoperating (below mean sea level, max) | –60.96 m to 12,192 m (–200 ft. to 40,000+ ft.) | |
| Operational Shock | 63 Gs max at 2 msec | |
| Non-Operational Shock | 350 Gs max at 2 msec | |

| Drive specification | ST380815AS | ST380215AS |
|--|--|------------|
| Vibration, operating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 0.5 Gs 350–500 Hz:: 0.25 Gs | |
| Vibration, nonoperating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 5.0 Gs 350–500 Hz:: 1.0 Gs | |
| Drive acoustics, sound power | | |
| Idle** | 2.8 bels (typical) 3.0 bels (max) | |
| Quiet seek | 3.0 bels (typical) 3.2 bels (max) | |
| Nonrecoverable read errors | 1 per 10 ¹⁴ bits read | |
| Annualized Failure Rate (AFR) | 0.34% | |
| Warranty | 5 years on distribution units. To determine the warranty for a specific drive, use a web browser to access the following web page: www.seagate.com/support/service/ From this page, click on the “Verify Your Warranty” link. You will be asked to provide the drive serial number, model number (or part number) and country of purchase. The system will display the warranty information for your drive. | |
| Contact start-stop cycles | 50,000 at 25°C, 50% rel. humidity | |
| Supports Hotplug operation per the Serial ATA Revision 2.5 specification | Yes | |

*One Gbyte equals one billion bytes when referring to hard drive capacity. Accessible capacity may vary depending on operating environment and formatting.

**During periods of drive idle, some offline activity may occur according to the S.M.A.R.T. specification, which may increase acoustic and power to operational levels.

Table 11: Drive specifications summary for the 40 Gbyte models

| Drive specification | ST340815AS | ST340215AS |
|---|---|------------|
| Formatted capacity (512 bytes/sector)* | 40 Gbytes | |
| Guaranteed sectors | 78,165,360 | |
| Heads | 1 | |
| Discs | 1 | |
| Bytes per sector | 512 | |
| Default sectors per track | 63 | |
| Default read/write heads | 16 | |
| Default cylinders | 16,383 | |
| Recording density | 824 kbits/in max | |
| Track density | 137.259 ktracks/in avg | |
| Areal density | 101 Gbits/in ² avg | |
| Spindle speed | 7,200 RPM | |
| Internal data transfer rate | 930 Mbits/sec max | |
| Sustained data transfer rate OD | 78 Mbytes/sec max | |
| I/O data-transfer rate | 300 Mbytes/sec max | |
| ATA data-transfer modes supported | PIO modes 0–4 Multiword DMA modes 0–2 Ultra DMA modes 0–6 | |
| Cache buffer | 8 Mbytes | 2 Mbytes |
| Height (max) | 19.99 mm (0.787 inches) | |
| Width (max) | 101.6 mm (4.000 inches) +/- 0.010 inches | |
| Length (max) | 146.99 mm (5.787 inches) | |
| Weight (typical) | 365 grams (0.805 lb.) | |
| Average latency | 4.16 msec | |
| Power-on to ready | 7.9 sec max | |
| Standby to ready | 7.9 sec max | |
| Track-to-track seek time | <1.0 msec typical read; <1.2 msec typical write | |
| Average seek, read | <11 msec typical | |
| Average seek, write | <12 msec typical | |
| Startup current (typical) 12V (peak) | 2.8 amps | |
| Voltage tolerance (including noise) | 5V ± 5% 12V ± 10% | |
| Ambient temperature | 0° to 60°C (operating) –40° to 75°C (nonoperating) | |
| Temperature gradient | 20°C per hour max (operating) 30°C per hour max (nonoperating) | |
| Relative humidity | 5% to 90% (operating) 5% to 95% (nonoperating) | |
| Relative humidity gradient | 30% per hour max | |
| Wet bulb temperature | 37.7°C max (operating) 40°C max (nonoperating) | |
| Altitude, operating | –60.96 m to 3,048 m (–200 ft. to 10,000+ ft.) | |
| Altitude, nonoperating (below mean sea level, max) | –60.96 m to 12,192 m (–200 ft. to 40,000+ ft.) | |
| Operational Shock | 63 Gs max at 2 msec | |
| Non-Operational Shock | 350 Gs max at 2 msec | |

| Drive specification | ST340815AS | ST340215AS |
|--|--|------------|
| Vibration, operating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 0.5 Gs 350–500 Hz:: 0.25 Gs | |
| Vibration, nonoperating | 5–22 Hz: 0.25 Gs, Limited displacement 22–350 Hz: 5.0 Gs 350–500 Hz:: 1.0 Gs | |
| Drive acoustics, sound power | | |
| Idle** | 2.8 bels (typical) 3.0 bels (max) | |
| Quiet seek | 3.0 bels (typical) 3.2 bels (max) | |
| Nonrecoverable read errors | 1 per 10 ¹⁴ bits read | |
| Annualized Failure Rate (AFR) | 0.34% | |
| Warranty | 5 years on distribution units. To determine the warranty for a specific drive, use a web browser to access the following web page: www.seagate.com/support/service/ From this page, click on the “Verify Your Warranty” link. You will be asked to provide the drive serial number, model number (or part number) and country of purchase. The system will display the warranty information for your drive. | |
| Contact start-stop cycles | 50,000 at 25°C, 50% rel. humidity | |
| Supports Hotplug operation per the Serial ATA Revision 2.5 specification | Yes | |

*One Gbyte equals one billion bytes when referring to hard drive capacity. Accessible capacity may vary depending on operating environment and formatting.

**During periods of drive idle, some offline activity may occur according to the S.M.A.R.T. specification, which may increase acoustic and power to operational levels.

2.2 Formatted capacity

| Model | Formatted capacity* | Guaranteed sectors | Bytes per sector |
|-------------|---------------------|--------------------|------------------|
| ST3750640AS | 750 Gbytes | 1,465,149,168 | 512 |
| ST3750840AS | 750 Gbytes | 1,465,149,168 | 512 |
| ST3500630AS | 500 Gbytes | 976,773,168 | 512 |
| ST3500830AS | 500 Gbytes | 976,773,168 | 512 |
| ST3400620AS | 400 Gbytes | 781,422,768 | 512 |
| ST3400820AS | 400 Gbytes | 781,422,768 | 512 |
| ST3320620AS | 320 Gbytes | 625,142,448 | 512 |
| ST3320820AS | 320 Gbytes | 625,142,448 | 512 |
| ST3300620AS | 300 Gbytes | 586,072,368 | 512 |
| ST3300820AS | 300 Gbytes | 586,072,368 | 512 |
| ST3250620AS | 250 Gbytes | 488,397,168 | 512 |
| ST3250820AS | 250 Gbytes | 488,397,168 | 512 |
| ST3250410AS | 250 Gbytes | 488,397,168 | 512 |
| ST3250310AS | 250 Gbytes | 488,397,168 | 512 |
| ST3200820AS | 200 Gbytes | 390,721,968 | 512 |
| ST3160815AS | 160 Gbytes | 312,581,808 | 512 |
| ST3160215AS | 160 Gbytes | 312,581,808 | 512 |
| ST3120815AS | 120 Gbytes | 234,441,648 | 512 |
| ST3120215AS | 120 Gbytes | 234,441,648 | 512 |
| ST380815AS | 80 Gbytes | 156,301,488 | 512 |
| ST380215AS | 80 Gbytes | 156,301,488 | 512 |
| ST340815AS | 40 Gbytes | 78,165,360 | 512 |
| ST340215AS | 40 Gbytes | 78,165,360 | 512 |

*One Gbyte equals one billion bytes when referring to hard drive capacity. Accessible capacity may vary depending on operating environment and formatting.

2.2.1 LBA mode

When addressing these drives in LBA mode, all blocks (sectors) are consecutively numbered from 0 to $n-1$, where n is the number of guaranteed sectors as defined above.

See Section 4.3.1, "Identify Device command" (words 60-61 and 100-103) for additional information about 48-bit addressing support of drives with capacities over 137 Gbytes.

2.3 Default logical geometry

| Cylinders | Read/write heads | Sectors per track |
|-----------|------------------|-------------------|
| 16,383 | 16 | 63 |

LBA mode

When addressing these drives in LBA mode, all blocks (sectors) are consecutively numbered from 0 to $n-1$, where n is the number of guaranteed sectors as defined above.

2.4 Recording and interface technology

| | Model capacity | | | | | | | | |
|---|-------------------|-------|-----|-----|-----|-----|---------|----|----|
| | 750 | 500 | 400 | 320 | 300 | 160 | 120 | 80 | 40 |
| Interface | Serial ATA (SATA) | | | | | | | | |
| Recording method | Perpendicular | | | | | | | | |
| Recording density (kbits/inch max) | 926 | 813 | 781 | | | | 824 | | |
| Track density (ktracks/inch avg) | 145 | | | | | | 137.259 | | |
| Areal density (Gbits/inch ² avg) | 128.2 | 114.4 | | | | | 101 | | |
| Spindle speed (RPM) | 7,200 ± 0.2% | | | | | | | | |
| Internal data transfer rate (Mbits/sec max) | 1,030 | | | | | | 930 | | |
| Sustained data transfer rate (Mbytes/sec max) | 78 | 72 | | | | | 78 | | |
| I/O data-transfer rate (Mbytes/sec max) | 300 | | | | | | | | |

| | Model capacity | | |
|---|----------------------------|-------------|----------------------------|
| | ST3250620AS ST3250820AS | ST3200820AS | ST3250410AS ST3250310AS |
| Interface | Serial ATA (SATA) | | |
| Recording method | Perpendicular | | |
| Recording density (kbits/inch max) | 813 | | 1,090 |
| Track density (ktracks/inch avg) | 145 | | 150 |
| Areal density (Gbits/inch ² avg) | 114.4 | | 164 |
| Spindle speed (RPM) | 7,200 ± 0.2% | | |
| Internal data transfer rate (Mbits/sec max) | 1,030 | | 1,287 |
| Sustained data transfer rate (Mbytes/sec max) | 72 | | 110 |
| I/O data-transfer rate (Mbytes/sec max) | 300 | | |

2.5 Physical characteristics

| | |
|---|-----------------------------------|
| Maximum height (4 and 3 disc models) | 26.1 mm (1.028 inches) |
| Maximum height (2 and 1 disc models) | 19.99 mm (0.787 inches) |
| Maximum width | 101.6 mm (4.000 +/- 0.010 inches) |
| Maximum length | 146.99 mm (5.787 inches) |
| Typical weight | |
| ST3750640AS and ST3750840AS | 720 grams (1.59 lbs) |
| ST3500630AS and ST3500830AS | |
| ST3400620AS and ST3400820AS | 635 grams (1.40 lbs) |
| ST3320620AS and ST3320820AS | |
| ST3300620AS and ST3300820AS | 600 grams (1.32 lbs) |
| ST3250620AS, ST3250820AS and ST3200820AS | |
| ST3160815AS, ST3160215AS, ST3120815AS and ST3120215AS, | 380 grams (0.838 lbs.) |
| ST3250410AS and ST3250310AS, | 382 grams (0.842 lbs) |
| ST380815AS, ST380215AS, ST340815AS and ST340215AS | 365 grams (0.805 lbs) |
| Cache buffer | |
| ST3750640AS, ST3500630AS, ST3400620AS, ST3320620AS, ST3300620AS, ST3250620AS and ST3250410AS | 16 Mbytes (16,384 kbytes) |
| ST3750840AS, ST3500830AS, ST3400820AS, ST3320820AS, ST3300820AS, ST3250820AS, ST3250310AS, ST3200820AS, ST3160815AS, ST3120815AS, ST380815AS and ST340815AS | 8 Mbytes (8,192 kbytes) |
| ST3160215AS, ST3120215AS, ST380215AS and ST340215AS | 2 Mbytes (2,048 kbytes) |

2.6 Seek time

Seek measurements are taken with nominal power at 25°C ambient temperature. All times are measured using drive diagnostics. The specifications in the table below are defined as follows:

- Track-to-track seek time is an average of all possible single-track seeks in both directions.
- Average seek time is a true statistical random average of at least 5,000 measurements of seeks between random tracks, less overhead.

| | 750 - 200 GB models* | | ST3250410AS and ST3250310AS* | | 160 - 40 GB models** | |
|---------------------------|----------------------|-------|------------------------------|-------|----------------------|-------|
| Typical seek times (msec) | Read | Write | Read | Write | Read | Write |
| Track-to-track | <0.8 | <1.0 | <1.0 | <1.2 | <1.0 | <1.2 |
| Average | <8.5 | <10.0 | <11.0 | <12.0 | <11.0 | <12.0 |
| Average latency: | 4.16 | | 4.16 | | | |

*Measured in performance mode.

**Measured in quiet mode.

Note. These drives are designed to consistently meet the seek times represented in this manual. Physical seeks, regardless of mode (such as track-to-track and average), are expected to meet the noted values. However, due to the manner in which these drives are formatted, benchmark tests that include command overhead or measure logical seeks may produce results that vary from these specifications.

2.7 Start/stop times

| | 750 - 320 GB models | 300 - 200 GB models | 160 - 40 GB models |
|-----------------------------|---------------------|---------------------|--------------------|
| Power-on to Ready (sec) | 15 (max) | 11 (max) | 7.9 (max) |
| Standby to Ready (sec) | 15 (max) | | 7.9 (max) |
| Ready to spindle stop (sec) | 10 (max) | | |

2.8 Power specifications

The drive receives DC power (+5V or +12V) through a native SATA power connector. See Figure 4 on page 40.

2.8.1 Power consumption

Power requirements for the drives are listed in the table on page 9. Typical power measurements are based on an average of drives tested, under nominal conditions, using 5.0V and 12.0V input voltage at 25°C ambient temperature.

- **Spinup power**

Spinup power is measured from the time of power-on to the time that the drive spindle reaches operating speed.

- **Seek mode**

During seek mode, the read/write actuator arm moves toward a specific position on the disc surface and does not execute a read or write operation. Servo electronics are active. Seek mode power represents the worst-case power consumption, using only random seeks with read or write latency time. This mode is not typical and is provided for worst-case information.

- **Read/write power and current**

Read/write power is measured with the heads on track, based on a 16-sector write followed by a 32-msec delay, then a 16-sector read followed by a 32-msec delay.

- **Operating power and current**

Operating power is measured using 40 percent random seeks, 40 percent read/write mode (1 write for each 10 reads) and 20 percent drive idle mode.

- **Idle mode power**

Idle mode power is measured with the drive up to speed, with servo electronics active and with the heads in a random track location.

- **Standby mode**

During Standby mode, the drive accepts commands, but the drive is not spinning, and the servo and read/write electronics are in power-down mode.

Table 12: DC power requirements

| Power dissipation (4-disc values shown) | Avg (watts 25° C) | Avg 5V typ amps | Avg 12V typ amps |
|--|-------------------|-----------------|------------------|
| Spinup | — | — | 2.8 (peak) |
| Idle* | 9.30 | 0.611 | 0.520 |
| Idle* (with offline activity) | 10.40 | 0.719 | 0.567 |
| Operating (40% r/w, 40% seek, 20% inop.) | 13.00 | 0.772 | 0.762 |
| Seeking (random, 20% idle) | 12.60 | 0.613 | 0.795 |
| Standby | 0.80 | 0.106 | 0.023 |
| Sleep | 0.80 | 0.106 | 0.023 |

*During periods of drive idle, some offline activity may occur according to the S.M.A.R.T. specification, which may increase acoustic and power to operational levels.

2.8.1.1 Typical current profiles




Figure 1. Typical 5V startup and operation current profile




Figure 2. Typical 12V startup and operation current profile

2.8.2 Conducted noise

Input noise ripple is measured at the host system power supply across an equivalent 80-ohm resistive load on the +12 volt line or an equivalent 15-ohm resistive load on the +5 volt line.

- Using 12-volt power, the drive is expected to operate with a maximum of 120 mV peak-to-peak square-wave injected noise at up to 10 MHz.
- Using 5-volt power, the drive is expected to operate with a maximum of 100 mV peak-to-peak square-wave injected noise at up to 10 MHz.

Note. Equivalent resistance is calculated by dividing the nominal voltage by the typical RMS read/write current.

2.8.3 Voltage tolerance

Voltage tolerance (including noise):

5V \pm 5%
12V \pm 10%

2.8.4 Power-management modes

The drive provides programmable power management to provide greater energy efficiency. In most systems, you can control power management through the system setup program. The drive features the following power-management modes:

| Power modes | Heads | Spindle | Buffer |
|-------------|----------|----------|----------|
| Active | Tracking | Rotating | Enabled |
| Idle | Tracking | Rotating | Enabled |
| Standby | Parked | Stopped | Enabled |
| Sleep | Parked | Stopped | Disabled |

- **Active mode**

The drive is in Active mode during the read/write and seek operations.

- **Idle mode**

The buffer remains enabled, and the drive accepts all commands and returns to Active mode any time disc access is necessary.

- **Standby mode**

The drive enters Standby mode when the host sends a Standby Immediate command. If the host has set the standby timer, the drive can also enter Standby mode automatically after the drive has been inactive for a specifiable length of time. The standby timer delay is established using a Standby or Idle command. In Standby mode, the drive buffer is enabled, the heads are parked and the spindle is at rest. The drive accepts all commands and returns to Active mode any time disc access is necessary.

- **Sleep mode**

The drive enters Sleep mode after receiving a Sleep command from the host. In Sleep mode, the drive buffer is disabled, the heads are parked and the spindle is at rest. The drive leaves Sleep mode after it receives a Hard Reset or Soft Reset from the host. After receiving a reset, the drive exits Sleep mode and enters Standby mode with all current translation parameters intact.

- **Idle and Standby timers**

Each time the drive performs an Active function (read, write or seek), the standby timer is reinitialized and begins counting down from its specified delay times to zero. If the standby timer reaches zero before any drive activity is required, the drive makes a transition to Standby mode. In both Idle and Standby mode, the drive accepts all commands and returns to Active mode when disc access is necessary.

2.9 Environmental specifications

2.9.1 Ambient temperature

Ambient temperature is defined as the temperature of the environment immediately surrounding the drive. Actual drive case temperature should not exceed 69°C (156°F) within the operating ambient conditions.

Above 1,000 feet (305 meters), the maximum temperature is derated linearly to 112°F (44°C) at 10,000 feet (3,048 meters).

| | |
|---------------|------------------------------|
| Operating: | 0° to 60°C (32° to 140°F) |
| Nonoperating: | –40° to 70°C (–40° to 158°F) |

2.9.2 Temperature gradient

| | |
|---------------|---|
| Operating: | 20°C per hour (68°F per hour max), without condensation |
| Nonoperating: | 30°C per hour (86°F per hour max) |

2.9.3 Humidity

2.9.3.1 Relative humidity

| | |
|---------------|--|
| Operating: | 5% to 90% noncondensing (30% per hour max) |
| Nonoperating: | 5% to 95% noncondensing (30% per hour max) |

2.9.3.2 Wet bulb temperature

| | |
|---------------|--|
| Operating: | 37.7°C (99.9°F max) |
| Nonoperating: | 200 - 750 GB models: 37.7°C (99.9°F max) 40 - 160 GB models: 40°C (104°F max) |

2.9.4 Altitude

| | |
|---------------|--|
| Operating: | –60.96 m to 3,048 m (–200 ft. to 10,000+ ft.) |
| Nonoperating: | –60.96 m to 12,192 m (–200 ft. to 40,000+ ft.) |

2.9.5 Shock

All shock specifications assume that the drive is mounted securely with the input shock applied at the drive mounting screws. Shock may be applied in the X, Y or Z axis.

2.9.5.1 Operating shock

These models (750GB, 500GB, 400GB, 320GB, 200GB, ST3250620AS and ST3250820AS) comply with the performance levels specified in this document when subjected to a maximum operating shock of 68 Gs based on half-sine shock pulses of 2 msec. Shocks should not be repeated more than two times per second.

These models (ST3250410AS, ST3250310AS, 160GB, 120GB, 80GB and 40GB) comply with the performance levels specified in this document when subjected to a maximum operating shock of 63 Gs based on half-sine shock pulses of 2 msec. Shocks should not be repeated more than two times per second.

2.9.5.2 Nonoperating shock

1 and 2 Disc models

The nonoperating shock level that the drive can experience without incurring physical damage or degradation in performance when subsequently put into operation is 350 Gs based on a nonrepetitive half-sine shock pulse of 2 msec duration.

3 and 4 Disc models

The nonoperating shock level that the drive can experience without incurring physical damage or degradation in performance when subsequently put into operation is 300 Gs based on a nonrepetitive half-sine shock pulse of 2 msec duration.

2.9.6 Vibration

All vibration specifications assume that the drive is mounted securely with the input vibration applied at the drive mounting screws. Vibration may be applied in the X, Y or Z axis.

2.9.6.1 Operating vibration

The maximum vibration levels that the drive may experience while meeting the performance standards specified in this document are specified below.

| | |
|------------|--------------------------------|
| 5–22 Hz | 0.25 Gs (Limited displacement) |
| 22–350 Hz | 0.50 Gs |
| 350–500 Hz | 0.25 Gs |

2.9.6.2 Nonoperating vibration

The maximum nonoperating vibration levels that the drive may experience without incurring physical damage or degradation in performance when subsequently put into operation are specified below.

| | |
|------------|--------------------------------|
| 5–22 Hz | 0.25 Gs (limited displacement) |
| 22–350 Hz | 5.0 Gs |
| 350–500 Hz | 1.0 Gs |

2.10 Acoustics

Drive acoustics are measured as overall A-weighted acoustic sound power levels (no pure tones). All measurements are consistent with ISO document 7779. Sound power measurements are taken under essentially free-field conditions over a reflecting plane. For all tests, the drive is oriented with the cover facing upward.

Note. For seek mode tests, the drive is placed in seek mode only. The number of seeks per second is defined by the following equation:

$$(\text{Number of seeks per second} = 0.4 / (\text{average latency} + \text{average access time}))$$

Table 13: Fluid Dynamic Bearing (FDB) motor acoustics

| | Idle* | Seek |
|---|----------------------------------|--|
| ST3750640AS, ST3750840AS, ST3500630AS, ST3500830AS | 2.8 bels (typ) 3.0 bels (max) | 3.7 bels (typ)** 3.9 bels (max)** |
| ST3400620AS, ST3400820AS | 2.7 bels (typ) 2.9 bels (max) | 3.4 bels (typ)** 3.6 bels (max)** |
| ST3320620AS, ST3320820AS, ST3300620AS, ST3300820AS, ST3250620AS, ST3250820AS, ST3200820AS | 2.5 bels (typ) 2.9 bels (max) | 3.0 bels (typ)** 3.2 bels (max)** |
| ST3250410AS, ST3250310AS | 2.8 bels (typ) 2.9 bels (max) | 3.0 bels (typ)*** 3.1 bels (max)*** |
| ST3160815AS, ST3160215AS, ST3120815AS, ST3120215AS, ST380815AS, ST380215AS, ST340815AS, ST340215AS | 2.8 bels (typ) 3.0 bels (max) | 3.0 bels (typ)*** 3.2 bels (max)*** |

*During periods of drive idle, some offline activity may occur according to the S.M.A.R.T. specification, which may increase acoustic and power to operational levels.

**Measured in performance mode.

***Measured in quiet mode.

2.11 Electromagnetic immunity

When properly installed in a representative host system, the drive operates without errors or degradation in performance when subjected to the radio frequency (RF) environments defined in the following table:

Table 14: Radio frequency environments

| Test | Description | Performance level | Reference standard |
|---------------------------|---|-------------------|-----------------------------------|
| Electrostatic discharge | Contact, HCP, VCP: ± 4 kV; Air: ± 8 kV | B | EN 61000-4-2: 95 |
| Radiated RF immunity | 80 to 1,000 MHz, 3 V/m, 80% AM with 1 kHz sine 900 MHz, 3 V/m, 50% pulse modulation @ 200 Hz | A | EN 61000-4-3: 96 ENV 50204: 95 |
| Electrical fast transient | ± 1 kV on AC mains, ± 0.5 kV on external I/O | B | EN 61000-4-4: 95 |
| Surge immunity | ± 1 kV differential, ± 2 kV common, AC mains | B | EN 61000-4-5: 95 |
| Conducted RF immunity | 150 kHz to 80 MHz, 3 Vrms, 80% AM with 1 kHz sine | A | EN 61000-4-6: 97 |
| Voltage dips, interrupts | 0% open, 5 seconds 0% short, 5 seconds 40%, 0.10 seconds 70%, 0.01 seconds | C C C B | EN 61000-4-11: 94 |

2.12 Reliability

2.12.1 Annualized Failure Rate (AFR) and Mean Time Between Failures (MTBF)

The product shall achieve an Annualized Failure Rate (AFR) of 0.34% (MTBF of 0.7 million hours) when operated in an environment of ambient air temperatures of 25°C. Operation at temperatures outside the specifications in Section 2.9 may increase the product AFR (decrease MTBF). AFR and MTBF are population statistics that are not relevant to individual units.

AFR and MTBF specifications are based on the following assumptions for desktop personal computer environments:

- 2400 power-on-hours per year.
- 10,000 average motor start/stop cycles per year.
- Operations at nominal voltages.
- Temperatures outside the specifications in Section 2.9 may reduce the product reliability.
- Normal I/O duty cycle for desktop personal computers. Operation at excessive I/O duty cycle may degrade product reliability.

The desktop personal computer environment of power-on-hours, temperature, and I/O duty cycle affect the product AFR and MTBF. The AFR and MTBF will be degraded if used in an enterprise application.

| | |
|-------------------------------|---|
| Nonrecoverable read errors | 1 per 10 ¹⁴ bits read, max |
| Annualized Failure Rate (AFR) | 0.34% (nominal power, 25°C ambient temperature) |
| Contact start-stop cycles | 50,000 cycles (at nominal voltage and temperature, with 60 cycles per hour and a 50% duty cycle) |
| Warranty | 5 years on distribution units. To determine the warranty for a specific drive, use a web browser to access the following web page: www.seagate.com/support/service/ From this page, click on the "Verify Your Warranty" link. You will be asked to provide the drive serial number, model number (or part number) and country of purchase. The system will display the warranty information for your drive. |
| Preventive maintenance | None required. |

2.13 Agency certification

2.13.1 Safety certification

The drives are recognized in accordance with UL 1950 and CSA C22.2 (950) and meet all applicable sections of IEC950 and EN 60950.

2.13.2 Electromagnetic compatibility

Hard drives that display the CE mark comply with the European Union (EU) requirements specified in the Electromagnetic Compatibility Directive (89/336/EEC). Testing is performed to the levels specified by the product standards for Information Technology Equipment (ITE). Emission levels are defined by EN 55022, Class B and the immunity levels are defined by EN 55024.

Drives are tested in representative end-user systems. Although CE-marked Seagate drives comply with the directives when used in the test systems, we cannot guarantee that all systems will comply with the directives. The drive is designed for operation inside a properly designed enclosure, with properly shielded I/O cable (if necessary) and terminators on all unused I/O ports. Computer manufacturers and system integrators should confirm EMC compliance and provide CE marking for their products.

Korean RRL

If these drives have the Korea Ministry of Information and Communication (MIC) logo, they comply with paragraph 1 of Article 11 of the Electromagnetic Compatibility control Regulation and meet the Electromagnetic Compatibility (EMC) Framework requirements of the Radio Research Laboratory (RRL) Ministry of Information and Communication Republic of Korea.

These drives have been tested and comply with the Electromagnetic Interference/Electromagnetic Susceptibility (EMI/EMS) for Class B products. Drives are tested in a representative, end-user system by a Korean-recognized lab.

- Family name: Barracuda 7200.10
- Certificate number: STX-L3510 (B)

Australian C-Tick (N176)

If these models have the C-Tick marking, they comply with the Australia/New Zealand Standard AS/NZS3548 1995 and meet the Electromagnetic Compatibility (EMC) Framework requirements of the Australian Communication Authority (ACA).

2.13.3 FCC verification

These drives are intended to be contained solely within a personal computer or similar enclosure (not attached as an external device). As such, each drive is considered to be a subassembly even when it is individually marketed to the customer. As a subassembly, no Federal Communications Commission verification or certification of the device is required.

Seagate has tested this device in enclosures as described above to ensure that the total assembly (enclosure, disc drive, motherboard, power supply, etc.) does comply with the limits for a Class B computing device, pursuant to Subpart J, Part 15 of the FCC rules. Operation with noncertified assemblies is likely to result in interference to radio and television reception.

Radio and television interference. This equipment generates and uses radio frequency energy and if not installed and used in strict accordance with the manufacturer's instructions, may cause interference to radio and television reception.

This equipment is designed to provide reasonable protection against such interference in a residential installation. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause interference to radio or television, which can be determined by turning the equipment on and off, you are encouraged to try one or more of the following corrective measures:

- Reorient the receiving antenna.
- Move the device to one side or the other of the radio or TV.
- Move the device farther away from the radio or TV.
- Plug the computer into a different outlet so that the receiver and computer are on different branch outlets.

If necessary, you should consult your dealer or an experienced radio/television technician for additional suggestions. You may find helpful the following booklet prepared by the Federal Communications Commission: *How to Identify and Resolve Radio-Television Interference Problems*. This booklet is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402. Refer to publication number 004-000-00345-4.

2.14 Environmental protection

Seagate designs its products to meet environmental protection requirements worldwide, including regulations restricting certain chemical substances.

2.14.1 European Union Restriction of Hazardous Substances (RoHS)

The European Union Restriction of Hazardous Substances (RoHS) Directive restricts the presence of chemical substances, including Lead (Pb), in electronic products effective July 2006. Although amendments to the European Union's Restriction of Hazardous Substances (RoHS) Directive have not been finalized, to the best of our knowledge the disc drives documented in this publication will comply with the final RoHS Directive requirements.

A number of parts and materials in Seagate products are procured from external suppliers. We rely on the representations of our suppliers regarding the presence of RoHS substances in these parts and materials. Our supplier contracts require compliance with our chemical substance restrictions, and our suppliers document their compliance with our requirements by providing material content declarations for all parts and materials for the disc drives documented in this publication. Current supplier declarations include disclosure of the inclusion of any RoHS-regulated substance in such parts or materials.

Seagate also has internal systems in place to ensure ongoing compliance with the RoHS Directive and all laws and regulations which restrict chemical content in electronic products. These systems include standard operating procedures that ensure that restricted substances are not utilized in our manufacturing operations, laboratory analytical validation testing, and an internal auditing process to ensure that all standard operating procedures are complied with.

2.15 Corrosive environment

Seagate electronic drive components pass accelerated corrosion testing equivalent to 10 years exposure to light industrial environments containing sulfurous gases, chlorine and nitric oxide, classes G and H per ASTM B845. However, this accelerated testing cannot duplicate every potential application environment. Users should use caution exposing any electronic components to uncontrolled chemical pollutants and corrosive chemicals as electronic drive component reliability can be affected by the installation environment. The silver, copper, nickel and gold films used in Seagate products are especially sensitive to the presence of sulfide, chloride, and nitrate contaminants. Sulfur is found to be the most damaging. In addition, electronic components should never be exposed to condensing water on the surface of the printed circuit board assembly (PCBA) or exposed to an ambient relative humidity greater than 95%. Materials used in cabinet fabrication, such as vulcanized rubber, that can outgas corrosive compounds should be minimized or eliminated. The useful life of any electronic equipment may be extended by replacing materials near circuitry with sulfide-free alternatives.

3.0 Configuring and mounting the drive

This section contains the specifications and instructions for configuring and mounting the drive.

3.1 Handling and static-discharge precautions

After unpacking, and before installation, the drive may be exposed to potential handling and electrostatic discharge (ESD) hazards. Observe the following standard handling and static-discharge precautions:

Caution:

- Before handling the drive, put on a grounded wrist strap, or ground yourself frequently by touching the metal chassis of a computer that is plugged into a grounded outlet. Wear a grounded wrist strap throughout the entire installation procedure.
- Handle the drive by its edges or frame *only*.
- The drive is extremely fragile—handle it with care. Do not press down on the drive top cover.
- Always rest the drive on a padded, antistatic surface until you mount it in the computer.
- Do not touch the connector pins or the printed circuit board.
- Do not remove the factory-installed labels from the drive or cover them with additional labels. Removal voids the warranty. Some factory-installed labels contain information needed to service the drive. Other labels are used to seal out dirt and contamination.

3.2 Configuring the drive

Each drive on the Serial ATA interface connects point-to-point with the Serial ATA host adapter. There is no master/slave relationship because each drive is considered a master in a point-to-point relationship. If two drives are attached on one Serial ATA host adapter, the host operating system views the two devices as if they were both “masters” on two separate ports. Both drives behave as if they are Device 0 (master) devices.

Serial ATA drives are designed for easy installation. It is usually not necessary to set any jumpers on the drive for proper operation; however, if you connect the drive and receive a “drive not detected” error, your SATA-equipped motherboard or host adapter may use a chipset that does not support SATA speed autonegotiation. If you have a motherboard or host adapter that does not support autonegotiation:

- Install a jumper as shown in Figure 3 below to limit the data transfer rate to 1.5 Gbits per second (and leave the drive connected to the SATA-equipped motherboard or host adapter that doesn't support autonegotiation) or
- Install a SATA host adapter that supports autonegotiation, leave the drive jumper block set to “Normal operation” (see Figure 3 below), and connect the drive to that adapter. This option has the benefit of not limiting the drive to a 1.5 Gbits/sec transfer rate.




Figure 3. Serial ATA connectors

3.3 Serial ATA cables and connectors

The Serial ATA interface cable consists of four conductors in two differential pairs, plus three ground connections. The cable size may be 30 to 26 AWG with a maximum length of one meter (39.37 inches). See Table 15 for connector pin definitions. Either end of the SATA signal cable can be attached to the drive or host.

For direct backplane connection, the drive connectors are inserted directly into the host receptacle. The drive and the host receptacle incorporate features that enable the direct connection to be hot pluggable and blind mateable.

For installations which require cables, you can connect the drive as illustrated in Figure 4.




Figure 4. Attaching SATA cabling

Each cable is keyed to ensure correct orientation. Barracuda 7200.10 Serial ATA drives support latching SATA connectors.

3.4 Drive mounting

You can mount the drive in any orientation using four screws in the side-mounting holes or four screws in the bottom-mounting holes. See Figures 5 and 6 for drive mounting dimensions. Follow these important mounting precautions when mounting the drive:

- Allow a minimum clearance of 0.030 inches (0.76 mm) around the entire perimeter of the drive for cooling.
- Use only 6-32 UNC mounting screws.
- The screws should be inserted no more than 0.150 inch (3.81 mm) into the bottom or side mounting holes.
- Do not overtighten the mounting screws (maximum torque: 6 inch-lb).




Figure 5. Mounting dimensions for 750-200 GB models (except ST3250410AS and ST3250310AS models)




Figure 6. Mounting dimensions for 160-40 GB models (including ST3250410AS and ST3250310AS models)

4.0 Serial ATA (SATA) interface

These drives use the industry-standard Serial ATA interface that supports FIS data transfers. It supports ATA programmed input/output (PIO) modes 0–4; multiword DMA modes 0–2, and Ultra DMA modes 0–6.

For detailed information about the Serial ATA interface, refer to the “Serial ATA: High Speed Serialized AT Attachment” specification.

4.1 Hot-Plug compatibility

Barracuda 7200.10 Serial ATA drives incorporate connectors which enable you to hot plug these drives in accordance with the Serial ATA Revision 2.5 specification. This specification can be downloaded from www.serialata.org.

4.2 Serial ATA device plug connector pin definitions

Table 15 summarizes the signals on the Serial ATA interface and power connectors..

Table 15: Serial ATA connector pin definitions

| Segment | Pin | Function | Definition |
|---------|-----|----------|-------------------------------------|
| Signal | S1 | Ground | 2nd mate |
| | S2 | A+ | Differential signal pair A from Phy |
| | S3 | A- | |
| | S4 | Ground | 2nd mate |
| | S5 | B- | Differential signal pair B from Phy |
| | S6 | B+ | |
| | S7 | Ground | 2nd mate |

Key and spacing separate signal and power segments

| | | | |
|-------|-----|----------------------|---|
| Power | P1 | V ₃₃ | 3.3V power |
| | P2 | V ₃₃ | 3.3V power |
| | P3 | V ₃₃ | 3.3V power, pre-charge, 2nd mate |
| | P4 | Ground | 1st mate |
| | P5 | Ground | 2nd mate |
| | P6 | Ground | 2nd mate |
| | P7 | V ₅ | 5V power, pre-charge, 2nd mate |
| | P8 | V ₅ | 5V power |
| | P9 | V ₅ | 5V power |
| | P10 | Ground | 2nd mate |
| | P11 | Ground or LED signal | If grounded, drive does not use deferred spin |
| | P12 | Ground | 1st mate. |
| | P13 | V ₁₂ | 12V power, pre-charge, 2nd mate |
| | P14 | V ₁₂ | 12V power |
| | P15 | V ₁₂ | 12V power |

Notes:

1. All pins are in a single row, with a 1.27 mm (0.050") pitch.
2. The comments on the mating sequence apply to the case of backplane blindmate connector only. In this case, the mating sequences are:
 - the ground pins P4 and P12.
 - the pre-charge power pins and the other ground pins.
 - the signal pins and the rest of the power pins.
3. There are three power pins for each voltage. One pin from each voltage is used for pre-charge when installed in a blind-mate backplane configuration.
4. All used voltage pins (V_x) must be terminated.

4.3 Supported ATA commands

The following table lists Serial ATA standard commands that the drive supports. For a detailed description of the ATA commands, refer to the Serial ATA: High Speed Serialized AT Attachment specification. See “S.M.A.R.T. commands” on page 52 for details and subcommands used in the S.M.A.R.T. implementation.

Table 16: Supported ATA commands

| Command name | Command code (in hex) |
|-------------------------------------|------------------------------------|
| Check Power Mode | 98 _H or E5 _H |
| Device Configuration Freeze Lock | B1 _H / C1 _H |
| Device Configuration Identify | B1 _H / C2 _H |
| Device Configuration Restore | B1 _H / C0 _H |
| Device Configuration Set | B1 _H / C3 _H |
| Device Reset | 08 _H |
| Download Microcode | 92 _H |
| Execute Device Diagnostics | 90 _H |
| Flush Cache | E7 _H |
| Flush Cache Extended | EA _H |
| Format Track | 50 _H |
| Identify Device | EC _H |
| Idle | 97 _H or E3 _H |
| Idle Immediate | 95 _H or E1 _H |
| Initialize Device Parameters | 91 _H |
| Read Buffer | E4 _H |
| Read DMA | C8 _H |
| Read DMA Extended | 25 _H |
| Read DMA Without Retries | C9 _H |
| Read Log Ext | 2F _H |
| Read Multiple | C4 _H |
| Read Multiple Extended | 29 _H |
| Read Native Max Address | F8 _H |
| Read Native Max Address Extended | 27 _H |
| Read Sectors | 20 _H |
| Read Sectors Extended | 24 _H |
| Read Sectors Without Retries | 21 _H |
| Read Verify Sectors | 40 _H |
| Read Verify Sectors Extended | 42 _H |
| Read Verify Sectors Without Retries | 41 _H |
| Recalibrate | 10 _H |
| Security Disable Password | F6 _H |
| Security Erase Prepare | F3 _H |

| Command name | Command code (in hex) |
|---|--|
| Security Erase Unit | F4 _H |
| Security Freeze | F5 _H |
| Security Set Password | F1 _H |
| Security Unlock | F2 _H |
| Seek | 70 _H |
| Set Features | EF _H |
| Set Max Address Note: Individual Set Max Address commands are identified by the value placed in the Set Max Features register as defined to the right. | F9 _H Address: 00 _H Password: 01 _H Lock: 02 _H Unlock: 03 _H Freeze Lock: 04 _H |
| Set Max Address Extended | 37 _H |
| Set Multiple Mode | C6 _H |
| Sleep | 99 _H or E6 _H |
| S.M.A.R.T. Disable Operations | B0 _H / D9 _H |
| S.M.A.R.T. Enable/Disable Autosave | B0 _H / D2 _H |
| S.M.A.R.T. Enable Operations | B0 _H / D8 _H |
| S.M.A.R.T. Execute Offline | B0 _H / D4 _H |
| S.M.A.R.T. Read Attribute Thresholds | B0 _H / D1 _H |
| S.M.A.R.T. Read Data | B0 _H / D0 _H |
| S.M.A.R.T. Read Log Sector | B0 _H / D5 _H |
| S.M.A.R.T. Return Status | B0 _H / DA _H |
| S.M.A.R.T. Save Attribute Values | B0 _H / D3 _H |
| S.M.A.R.T. Write Log Sector | B0 _H / D6 _H |
| Standby | 96 _H or E2 _H |
| Standby Immediate | 94 _H or E0 _H |
| Write Buffer | E8 _H |
| Write DMA | CA _H |
| Write DMA Extended | 35 _H |
| Write DMA FUA Extended | CD _H |
| Write DMA Without Retries | CB _H |
| Write Log Extended | 3F _H |
| Write Multiple | C5 _H |
| Write Multiple Extended | 39 _H |
| Write Multiple FUA Extended | CE _H |
| Write Sectors | 30 _H |
| Write Sectors Without Retries | 31 _H |
| Write Sectors Extended | 34 _H |

4.3.1 Identify Device command

The Identify Device command (command code EC_H) transfers information about the drive to the host following power up. The data is organized as a single 512-byte block of data, whose contents are shown in Table 16 on page 45. All reserved bits or words should be set to zero. Parameters listed with an “x” are drive-specific or vary with the state of the drive. See Section 2.0 on page 3 for default parameter settings.

The following commands contain drive-specific features that may not be included in the Serial ATA specification.

| Word | Description | Value |
|-------|--|-------------------|
| 0 | Configuration information: <ul style="list-style-type: none">• Bit 15: 0 = ATA; 1 = ATAPI• Bit 7: removable media• Bit 6: removable controller• Bit 0: reserved | 0C5A _H |
| 1 | Number of logical cylinders | 16,383 |
| 2 | ATA-reserved | 0000 _H |
| 3 | Number of logical heads | 16 |
| 4 | Retired | 0000 _H |
| 5 | Retired | 0000 _H |
| 6 | Number of logical sectors per logical track: 63 | 003F _H |
| 7–9 | Retired | 0000 _H |
| 10–19 | Serial number: (20 ASCII characters, 0000 _H = none) | ASCII |
| 20 | Retired | 0000 _H |
| 21 | Retired | 0400 _H |
| 22 | Obsolete | 0000 _H |
| 23–26 | Firmware revision (8 ASCII character string, padded with blanks to end of string) | x.xx |
| 27–46 | Drive model number: (40 ASCII characters, padded with blanks to end of string) | |
| 47 | (Bits 7–0) Maximum sectors per interrupt on Read multiple and Write multiple (16) | 8010 _H |
| 48 | Reserved | 0000 _H |
| 49 | Standard Standby timer, IORDY supported and may be disabled | 2F00 _H |
| 50 | ATA-reserved | 0000 _H |
| 51 | PIO data-transfer cycle timing mode | 0200 _H |
| 52 | Retired | 0200 _H |
| 53 | Words 54–58, 64–70 and 88 are valid | 0007 _H |
| 54 | Number of current logical cylinders | xxxx _H |
| 55 | Number of current logical heads | xxxx _H |
| 56 | Number of current logical sectors per logical track | xxxx _H |
| 57–58 | Current capacity in sectors | xxxx _H |
| 59 | Number of sectors transferred during a Read Multiple or Write Multiple command | xxxx _H |

| Word | Description | Value |
|-------|--|-------------------|
| 60–61 | Total number of user-addressable LBA sectors available (see Section 2.2 for related information) *Note: The maximum value allowed in this field is: 0FFFFFFFh (268,435,455 sectors, 137 Gbytes). Drives with capacities over 137 Gbytes will have 0FFFFFFFh in this field and the actual number of user-addressable LBAs specified in words 100-103. This is required for drives that support the 48-bit addressing feature. | 0FFFFFFFh* |
| 62 | Retired | 0000 _H |
| 63 | Multiword DMA active and modes supported (see note following this table) | xx07 _H |
| 64 | Advanced PIO modes supported (modes 3 and 4 supported) | 0003 _H |
| 65 | Minimum multiword DMA transfer cycle time per word (120 nsec) | 0078 _H |
| 66 | Recommended multiword DMA transfer cycle time per word (120 nsec) | 0078 _H |
| 67 | Minimum PIO cycle time without IORDY flow control (240 nsec) | 00F0 _H |
| 68 | Minimum PIO cycle time with IORDY flow control (120 nsec) | 0078 _H |
| 69–74 | ATA-reserved | 0000 _H |
| 75 | Queue depth | 0000 _H |
| 76 | Serial ATA capabilities | xxxx _H |
| 77 | Reserved for future Serial ATA definition | xxxx _H |
| 78 | Serial ATA features supported | xxxx _H |
| 79 | Serial ATA features enabled | xxxx _H |
| 80 | Major version number | 003E _H |
| 81 | Minor version number | 0000 _H |
| 82 | Command sets supported | 364B _H |
| 83 | Command sets supported | 7C03 _H |
| 84 | Command sets support extension | 4003 _H |
| 85 | Command sets enabled | 30xx _H |
| 86 | Command sets enabled | 0001 _H |
| 87 | Command sets enable extension | 4000 _H |
| 88 | Ultra DMA support and current mode (see note following this table) | xx3F _H |
| 89 | Security erase time | 0000 _H |
| 90 | Enhanced security erase time | 0000 _H |
| 92 | Master password revision code | FFFE _H |
| 93 | Hardware reset value (see description following this table) | xxxx _H |
| 95–99 | ATA-reserved | 0000 _H |

| Word | Description | Value |
|---------|--|---|
| 100–103 | Total number of user-addressable LBA sectors available (see Section 2.2 for related information). These words are required for drives that support the 48-bit addressing feature. Maximum value: 0000FFFFFFFFFh. | ST3750640AS = 1,465,149,168 ST3750840AS = 1,465,149,168 ST3500630AS = 976,773,168 ST3500830AS = 976,773,168 ST3400620AS = 781,422,768 ST3400820AS = 781,422,768 ST3320620AS = 625,142,448 ST3320820AS = 625,142,448 ST3300620AS = 586,072,368 ST3300820AS = 586,072,368 ST3250620AS = 488,397,168 ST3250820AS = 488,397,168 ST3250410AS = 488,397,168 ST3250310AS = 488,397,168 ST3200820AS = 390,721,968 ST3160815AS = 312,581,808 ST3160215AS = 312,581,808 ST3120815AS = 234,441,648 ST3120215AS = 234,441,648 ST380815AS = 156,301,488 ST380215AS = 156,301,488 ST340815AS = 78,165,360 ST340215AS = 78,165,360 |
| 104–127 | ATA-reserved | 0000 _H |
| 128 | Security status | 0001 _H |
| 129–159 | Seagate-reserved | xxxx _H |
| 160–254 | ATA-reserved | 0000 _H |
| 255 | Integrity word | xxA5 _H |

Note. Advanced Power Management (APM) and Automatic Acoustic Management (AAM) features are not supported

Note. See the bit descriptions below for words 63, 88, and 93 of the Identify Drive data.

| Description (if bit is set to 1) | | |
|----------------------------------|-----|---|
| | Bit | Word 63 |
| | 0 | Multiword DMA mode 0 is supported. |
| | 1 | Multiword DMA mode 1 is supported. |
| | 2 | Multiword DMA mode 2 is supported. |
| | 8 | Multiword DMA mode 0 is currently active. |
| | 9 | Multiword DMA mode 1 is currently active. |
| | 10 | Multiword DMA mode 2 is currently active. |
| | Bit | Word 88 |
| | 0 | Ultra DMA mode 0 is supported. |
| | 1 | Ultra DMA mode 1 is supported. |
| | 2 | Ultra DMA mode 2 is supported. |
| | 3 | Ultra DMA mode 3 is supported. |
| | 4 | Ultra DMA mode 4 is supported. |
| | 5 | Ultra DMA mode 5 is supported. |
| | 6 | Ultra DMA mode 6 is supported. |
| | 8 | Ultra DMA mode 0 is currently active. |
| | 9 | Ultra DMA mode 1 is currently active. |
| | 10 | Ultra DMA mode 2 is currently active. |
| | 11 | Ultra DMA mode 3 is currently active. |
| | 12 | Ultra DMA mode 4 is currently active. |
| | 13 | Ultra DMA mode 5 is currently active. |
| | 14 | Ultra DMA mode 6 is currently active. |

4.3.2 Set Features command

This command controls the implementation of various features that the drive supports. When the drive receives this command, it sets BSY, checks the contents of the Features register, clears BSY and generates an interrupt. If the value in the register does not represent a feature that the drive supports, the command is aborted. Power-on default has the read look-ahead and write caching features enabled. The acceptable values for the Features register are defined as follows:

Table 17: Set Features command values

| | |
|-----------------|---|
| 02 _H | Enable write cache (<i>default</i>). |
| 03 _H | Set transfer mode (based on value in Sector Count register). Sector Count register values: |
| 00 _H | Set PIO mode to default (PIO mode 2). |
| 01 _H | Set PIO mode to default and disable IORDY (PIO mode 2). |
| 08 _H | PIO mode 0 |
| 09 _H | PIO mode 1 |
| 0A _H | PIO mode 2 |
| 0B _H | PIO mode 3 |
| 0C _H | PIO mode 4 (<i>default</i>) |
| 20 _H | Multiword DMA mode 0 |
| 21 _H | Multiword DMA mode 1 |
| 22 _H | Multiword DMA mode 2 |
| 40 _H | Ultra DMA mode 0 |
| 41 _H | Ultra DMA mode 1 |
| 42 _H | Ultra DMA mode 2 |
| 43 _H | Ultra DMA mode 3 |
| 44 _H | Ultra DMA mode 4 |
| 45 _H | Ultra DMA mode 5 |
| 46 _H | Ultra DMA mode 6 |
| 10 _H | Enable use of SATA features |
| 55 _H | Disable read look-ahead (read cache) feature. |
| 82 _H | Disable write cache |
| 90 _H | Disable use of SATA features |
| AA _H | Enable read look-ahead (read cache) feature (<i>default</i>). |
| F1 _H | Report full capacity available |

Note. At power-on, or after a hardware or software reset, the default values of the features are as indicated above.

4.3.3 S.M.A.R.T. commands

S.M.A.R.T. provides near-term failure prediction for disc drives. When S.M.A.R.T. is enabled, the drive monitors predetermined drive attributes that are susceptible to degradation over time. If self-monitoring determines that a failure is likely, S.M.A.R.T. makes a status report available to the host. Not all failures are predictable. S.M.A.R.T. predictability is limited to the attributes the drive can monitor. For more information on S.M.A.R.T. commands and implementation, see the *Draft ATA-5 Standard*.

SeaTools diagnostic software activates a built-in drive self-test (DST S.M.A.R.T. command for D4_H) that eliminates unnecessary drive returns. The diagnostic software ships with all new drives and is also available at: <http://seatools.seagate.com>.

This drive is shipped with S.M.A.R.T. features disabled. You must have a recent BIOS or software package that supports S.M.A.R.T. to enable this feature. The table below shows the S.M.A.R.T. command codes that the drive uses.

Table 18: S.M.A.R.T. commands

| Code in features register | S.M.A.R.T. command |
|---------------------------|--|
| D0 _H | S.M.A.R.T. Read Data |
| D2 _H | S.M.A.R.T. Enable/Disable Attribute Autosave |
| D3 _H | S.M.A.R.T. Save Attribute Values |
| D4 _H | S.M.A.R.T. Execute Off-line Immediate (runs DST) |
| D5 _H | S.M.A.R.T. Read Log Sector |
| D6 _H | S.M.A.R.T. Write Log Sector |
| D8 _H | S.M.A.R.T. Enable Operations |
| D9 _H | S.M.A.R.T. Disable Operations |
| DA _H | S.M.A.R.T. Return Status |

Note. If an appropriate code is not written to the Features Register, the command is aborted and 0x04 (abort) is written to the Error register.

5.0 Seagate Technology support services

Online services

Internet

For information regarding Seagate products and services, visit www.seagate.com. Worldwide support is available 24 hours daily by email for your questions.

Presales Support:

Presales@Seagate.com

Technical Support:

DiscSupport@Seagate.com

Warranty Support:

<http://www.seagate.com/support/service/index.html>

mySeagate

my.seagate.com is the industry's first Web portal designed specifically for OEMs and distributors. It provides self-service access to critical applications, personalized content and the tools that allow our partners to manage their Seagate account functions. Submit pricing requests, orders and returns through a single, password-protected Web interface-anytime, anywhere in the world.

spp.seagate.com

spp.seagate.com supports Seagate resellers with product information, program benefits and sales tools. You may register for customized communications that are not available on the web. These communications contain product launch, EOL, pricing, promotions and other channel-related information. To learn more about the benefits or to register, go to spp.seagate.com, any time, from anywhere in the world.

Seagate Service Centers

Presales Support

Our Presales Support staff can help you determine which Seagate products are best suited for your specific application or computer system, as well as product availability and compatibility.

Technical Support

Seagate technical support is available to assist you online at support.seagate.com or through one of our call centers. Have your system configuration information and your "ST" model number available.

SeaTDD™ (+1-405-324-3655) is a telecommunications device for the deaf (TDD). You can send questions or comments 24 hours daily and exchange messages with a technical support specialist during normal business hours for the call center in your region.

Customer Service Operations

Warranty Service

Seagate offers worldwide customer support for Seagate products. Seagate distributors, OEMs and other direct customers should contact their Seagate Customer Service Operations (CSO) representative for warranty-related issues. Resellers or end users of drive products should contact their place of purchase or Seagate warranty service for assistance. Have your serial number and model or part number available.

Data Recovery Services

Seagate offers data recovery services for all formats and all brands of storage media. Our data recovery services labs are currently located throughout the world. . Additional information, including an online request form and data loss prevention resources, is available at <http://services.seagate.com/index.aspx>

Authorized Service Centers

Seagate Service Centers are available on a global basis for the return of defective products. Contact your customer support representative for the location nearest you.

USA/Canada/Latin America support services

For an extensive list of telephone numbers to technical support, presales and warranty service in USA/Canada/Latin America, including business hours, go to the "Contact Us" page on www.seagate.com.

Global Customer Support

Presales, Technical, and Warranty Support

| Call Center | Toll-free | Direct dial |
|----------------------------|---------------|-----------------|
| USA, Canada, and Mexico | 1-800-SEAGATE | +1-405-324-4700 |

Data Recovery Services

| Call Center | Toll-free | Direct dial | FAX |
|----------------------------|-----------------|-----------------|-----------------------------------|
| USA, Canada, and Mexico | 1-800-475-01435 | +1-905-474-2162 | 1-800-475-0158 +1-905-474-2459 |

Europe, the Middle East and Africa Support Services

For an extensive list of telephone numbers to technical support, presales and warranty service in Europe, the Middle East and Africa, go to the "Contact Us" page on www.seagate.com.

Asia/Pacific Support Services

For an extensive list of telephone numbers to technical support, presales and warranty service in Asia/Pacific, go to the "Contact Us" page on www.seagate.com.

Publication feedback survey

We are interested in your comments and suggestions regarding this publication. Please take a few minutes to participate in our survey at the following URL:

<http://survey.seagate.com/survey/techpubs.nsf>

Thank you for your time and comments.

Index

A

- ACA 37
- acceleration 34
- acoustics 35
- Active 32
- Active mode 32
- actuator arm 30
- AFR 36
- Agency certification 36
- altitude 33
- Ambient temperature 33
- ambient temperature 29, 30
- Annualized Failure Rate 36
- Annualized Failure Rate (AFR) 36
- areal density 1, 27
- ATA commands 45
- Australia/New Zealand Standard AS/NZS3548 1995 37
- Australian Communication Authority (ACA) 37
- Australian C-Tick 37
- Average latency 29
- Average seek time 29

B

- buffer 28

C

- cables and connectors 40
- cache 28
- capacity 26
- case temperature 33
- CE mark 36
- certification 36
- Check Power Mode 45
- compatibility 36
- Conducted noise 31
- Conducted RF immunity 35
- Configuring the drive 39
- connectors 40
- Corrosive environment 38
- CSA C22.2 (950) 36
- cycles 36
- Cylinders 27

D

- data-transfer rates 1
- DC power 30
- Default logical geometry 27
- density 27
- Device Configuration Freeze Lock 45

- Device Configuration Identify 45
- Device Configuration Restore 45
- Device Configuration Set 45
- Device Reset 45
- dimensions 41, 42
- disc surface 30
- dissipation 30
- Download Microcode 45
- duty cycle 36

E

- Electrical fast transient 35
- Electromagnetic compatibility 36
- Electromagnetic Compatibility (EMC) 37
- Electromagnetic Compatibility control Regulation 37
- Electromagnetic Compatibility Directive (89/336/EEC) 36
- Electromagnetic immunity 35
- Electrostatic discharge 35
- electrostatic discharge (ESD) 39
- EN 55022, Class B 36
- EN 55024 36
- EN 60950 36
- enclosures 37
- Environmental specifications 33
- EPRML 1
- error-correction algorithms 1
- errors 36
- ESD 39
- EU 36
- European Union (EU) requirements 36
- Execute Device Diagnostics 45

F

- FCC verification 37
- features 1
- Flush Cache 45
- Flush Cache Extended 45
- Format Track 45
- Formatted capacity 26

G

- geometry 27
- Gs 34
- guaranteed sectors 26, 27

H

- Handling precautions 39
- heads 27
- height 28
- humidity 33

I

- I/O data-transfer rate 27
- I/O duty cycle 36
- Identify Device 45
- Identify Device command 47
- Idle 32, 45
- Idle Immediate 45
- Idle mode 30, 32
- IEC950 36
- Information Technology Equipment (ITE) 36
- Initialize Device Parameters 45
- Input noise ripple 31
- input voltage 30
- interface 27, 43
- interference 37
- internal data-transfer rate OD 27
- is 29
- ISO document 7779 35
- ITE 36

K

- Korea Ministry of Information and Communication (MIC) 37
- Korean RRL 37

L

- latency 29
- latency time 30
- LBA mode 26, 27
- length 28
- logical geometry 27

M

- maintenance 36
- master/slave 2
- maximum temperature 33
- Mean Time Between Failures 36
- MIC 37
- mounting 41
- mounting screws 33
- mounting the drive 39
- MTBF 36

N

- noise 31
- nominal power 29
- Nonoperating shock 34
- Nonoperating vibration 34
- Nonrecoverable read errors 36

O

- operating 30

- Operating power 30
- Operating shock 33
- Operating vibration 34

P

- Physical characteristics 28
- point-to-point 2, 40
- Power consumption 30
- power consumption 30
- power dissipation 30
- Power modes 32
- Power specifications 30
- Power-management modes 32
- Power-on to Ready 29
- power-on-hours 36
- precautions 39
- printed circuit board 39
- programmable power management 32

Q

- quick reference 3

R

- Radiated RF immunity 35
- radio and television interference 37
- radio frequency (RF) 35
- random seeks 30
- Read Buffer 45
- Read DMA 45
- Read DMA Extended 45
- Read DMA without Retries 45
- read errors 36
- Read Log Ext 45
- Read Multiple 45
- Read Multiple Extended 45
- Read Native Max Address 45
- Read Native Max Address Extended 45
- Read Sectors 45
- Read Sectors Extended 45
- Read Sectors Without Retries 45
- Read Verify Sectors 45
- Read Verify Sectors Extended 45
- Read Verify Sectors Without Retries 45
- read/write actuator arm 30
- Read/write heads 27
- Read/write power 30
- Recalibrate 45
- recording density 27
- recording method 27
- Recording technology 27
- relative humidity 33
- Reliability 36
- RF 35
- RMS read/write current 31

RoHS 38
RRL 37

S

S.M.A.R.T. Disable Operations 46
S.M.A.R.T. Enable Operations 46
S.M.A.R.T. Enable/Disable Autosave 46
S.M.A.R.T. Execute Offline 46
S.M.A.R.T. implementation 45
S.M.A.R.T. Read Attribute Thresholds 46
S.M.A.R.T. Read Data 46
S.M.A.R.T. Read Log Sector 46
S.M.A.R.T. Return Status 46
S.M.A.R.T. Save Attribute Values 46
S.M.A.R.T. Write Log sector 46
Safety certification 36
SATA 43
screws 33
sectors 26
Sectors per track 27
Security Disable Password 45
Security Erase Prepare 45
Security Erase Unit 46
Security Freeze 46
Security Set Password 46
Security Unlock 46
Seek 46
seek mode 30
Seek mode power 30
Seek time 29
Seeking 30
Serial ATA (SATA) interface 43
serial ATA ports 2
Servo electronics 30
servo electronics 30
Set Features 46
Set Max Address 46
Set Max Address Extended 46
Set Multiple Mode 46
Shock 33
single-track seeks 29
Sleep 30, 32, 46
Sleep mode 32
sound 35
Specification summary table 3
spindle speed 27
Spinup 30
Spinup power 30
Standby 30, 32, 46
Standby Immediate 46
Standby mode 30, 32
standby timer 32
Standby to Ready 29
Start/stop times 29
start-stop cycles 36

static-discharge 39
subassembly 37
support services 53
Surge immunity 35

T

technical support services 53
temperature 29, 33
temperature gradient 33
timer 32
timers 32
track density 27
Track-to-track 29
Track-to-track seek time 29
tunneling magnetoresistive (TGMR) recording heads
1

U

UL 1950 36

V

Vibration 34
voltage 30
Voltage dips, interrupts 35
Voltage tolerance 31

W

Warranty 36
weight 28
wet bulb temperature 33
width 28
Write Buffer 46
Write DMA 46
Write DMA Extended 46
Write DMA FUA Extended 46
Write DMA Without Retries 46
Write Log Extended 46
Write Multiple 46
Write Multiple Extended 46
Write Multiple FUA Extended 46
Write Sectors 46
Write Sectors Extended 46
Write Sectors Without Retries 46



Seagate Technology LLC
920 Disc Drive, Scotts Valley, California 95066-4544, USA
Publication Number: 100402371, Rev. F, Printed in USA